

SLI028026CW_PW_AW

SLI028026CW_PW_AW



Power	52 W	Voltage	230 V
Luminous flux*	8900 lm (360°)	Colour temperature	6000 K
Colour of light	CW	Beam angle	120 °
IK	09	Degree of protection (IP)	IP65

Technical data

Code	SLI028026CW_PW_AW
Power	52 W
Nominal current	235 mA
Voltage	230 V
Energy consumption	52 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.92
Useful luminous flux*	8900 lm (360°)
Luminous flux**	8000 lm (360°)
Lamp efficacy	171 lm/W
Luminous intensity	2500 cd
Colour temperature	6000 K
Colour of light	CW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	09
Degree of protection (IP)	IP65
Colour	Gray/White
Dimension (AxBxC)	1490x72x70 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 16 pcs per line, emergency module ,

