



MASTER TL5 High Efficiency Eco

MASTER TL5 HE Eco 13=14W/830 UNP/40

This extremely efficient TL5 lamp (tube diameter 16 mm) saves considerable energy by simple lamp-for-lamp replacement. The TL5 HE Eco lamp offers excellent lumen maintenance and color rendering. Application areas vary from offices and industry to schools and retail environments.

Warnings and Safety

- A reduction in energy consumption is only achieved with current-controlled gear.
- The lamps operate perfectly with power-controlled gear, but in that case the light output can be up to 10% higher.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap-Base	G5 [G5]
Features	na [Not Applicable]
Flux measurement reference	Sphere

Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux	1,150 lumen
Color Designation	Warm White (WW)
Chromaticity Coordinate X (Nom)	0.44
Chromaticity Coordinate Y (Nom)	0.403
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	92 lm/W

Color rendering index (CRI)	82
-----------------------------	----

Operating and Electrical	
Power Consumption	12.5 W
Lamp Current (Nom)	0.170 A

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Shape	T5 [16 mm (T5)]


Approval and Application	
Mercury (Hg) Content (Nom)	1.2 mg

MASTER TL5 High Efficiency Eco

Energy Consumption kWh/1000 h	13 kWh
EPREL Registration Number	423,462
Product Data	
Full product code	872790088081600
Order product name	MASTER TL5 HE Eco 13=14W/830 UNP/40
Order code	927989883031


Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	40
Material number (12NC)	927989883031
Full product name	MASTER TL5 HE Eco 13=14W/830 UNP/40
EAN/UPC - Case	8727900880816

Dimensional drawing




Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL5 HE Eco 13=14W/830 UNP/40	17 mm	549.0 mm	556.1 mm	553.7 mm	563.2 mm

Photometric data



Spectral Power Distribution Colour - MASTER TL5 HE Eco 13=14W/830 UNP/40

Lifetime




Life Expectancy Diagram - MASTER TL5 HE Eco 13=14W/830 UNP/40

Life Expectancy Diagram - MASTER TL5 HE Eco 13=14W/830 UNP/40

MASTER TL5 High Efficiency Eco

Lifetime



Lumen Maintenance Diagram - MASTER TL5 HE Eco 13=14W/830 UNP/40

