



product description: it is used to divide the interior of the trunkings, thus allowing a better manipulation with the inserted cables and clarity  
 installation is done by „click” onto „T”-rail on trunking’s bottom  
 possibility to install in places with risk of flammable gases and vapor – danger zone 2  
 possibility to install in places with explosive risk of dust – danger zone 22

item number: PEKD 40\_-C  
 material: PVC - Pb-free  
 self-snuffing: yes, within 30 s  
 temperature resistance: -5 - +60 °C  
 color: white  
 length: 2 m  
 length tolerance: ±10 mm  
 package: 2m / 20m / 120 m  
 weight: 0,1 kg/m  
 meets the requiremetns: EN 50085-1 ed.2:06, EN 50085-2-1:07  
 storage: ČSN 64 0090



chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate  
 NO: aceton, benzen, chlorinated hydrocarbons, tetrachlorocarbon

compatible with: LH 60X40  
 EKD 80X40  
 EKD 100X40  
 EKD 120X40