


Screw

terminal block 2.5mm², 2+2, 1-level, beige color

| | |
|---|---|
| Series | CBR |
| Code | CR110 |
| Type | CBR.2 |
| HS code | 85369010 |
| Colour | Beige |
| TECHNICAL FEATURES | |
| Function/Type | Feed-through (distributor 2 IN / 2 OUT) |
| Rated cross-section | 2.5 mm ² |
| Connecting capacity | |
| Flexible wire | 0.2-4 mm ² |
| Rigid wire | 0.2-4 mm ² |
| Wire with ferrule - ferrule type | 2.5 mm ² – WP25/14 |
| Electrical characteristics according to IEC EN standard | |
| Maximum voltage AC/DC | 800 V |
| Maximum current (rated cross-section) | 24 A |
| Caliber | A3 |
| Electrical characteristics according to UL Standard | |
| Maximum voltage AC/DC | 600 V |
| Maximum current (rated cross-section) | 15 A |
| Section (min-max) | 20-14 (AWG) |
| Tightening torque value (UL) | 5.5 lb.in |
| Electrical characteristics according to ATEX directive and IEC Ex standard | |
| Maximum voltage AC/DC | – |
| Maximum current (rated cross-section) | – |
| Operating temperature Min/Max | -40 °C / +110 °C |
| Rated impulse withstand voltage / pollution degree | 8 kV / 3 |
| Insulation stripping length | 8 mm |
| Tightening torque value (nom. / max.) | 0.4 / 0.5 Nm |
| Width (pitch) | 5 mm |
| Length | 43 mm |
| Height mounted on TH35-7.5/TH35-15/G32 | 52 / 60 / 56 mm |
| Insulation material temperature index (EN 60216-1) | 130 °C |
| Plastic material | Polyamide UL94V-0 |
| ACCESSORIES | |
| End section | |
| Grey | CBR/PT/GR (cod. CR111GR) |
| Blue | – |
| Beige | CBR/PT (cod. CR111) |
| Thickness | 1.5 mm |
| Cross-connection | |
| Model A) | PM/25/... (cod. PM25...) |
| Model B) | – |
| Rated current carrying capacity IEC/ATEX | 24 A |
| Cross-connection identification strip | – |
| Multiple cross-connection bar | PMP/25 (cod. PMP25) |
| Shunting screw and sleeve (Standard / Exe) | CPM/25 (cod. CPM25) |
| Protection cover | PRP/5 (cod. PRP05) |
| Coloured partition plate | DFU/4/R (cod. DU04R) |
| Test plug socket | SDD/1 (cod. DD001) – PSD/K (cod. PD011) |
| End section for modular test plug | – |
| Marking | |
| Single marking tag | CNU/8/51 (cod. NU0851S) |
| Single marking tag for pitch insertion | – |
| Warning plate | – |
| End bracket | |
| TH35 screw type | BT/3 (cod. BT003) |
| TH35 snap-fit type | BTO (cod. BT007) |
| TH35 and G32 snap-fit type | BTU (cod. BT005) |
| Mounting rail | |
| IEC 60715/TH35 | PR/3/... |
| IEC 60715/G32 | PR/DIN/... |
| APPROVALS AND MARKINGS | |



1 For more details on accessories, refer to the relevant chapters

DESCRIZIONE DEL PRODOTTO

CBR.2 Screw terminal block 2.5mm², 2+2, 1-level, beige color