

PSK 10 85 SQL (784 085)

- Earthing and short-circuiting devices can be configured online via the earthing and short-circuiting configurator
- For connecting the phase cables of single-pole and three-pole earthing and short-circuiting devices to the overhead line
- With long threaded T pin shaft
- Wide clamping range



Figure without obligation




Figure without obligation

| Type | PSK 10 85 SQL |
|---|---|
| Part No. | 784 085 |
| Clamping range Ø | 10 ... 85 mm |
| Anti-rotation element | PK2 |
| For cable cross-section Cu | 16 ... 150 mm ² |
| Max. short-circuit current I _k 0.5 s | 29.6 kA |
| Max. short-circuit current I _k 1 s | 29.6 kA |
| Standard | EN/IEC 61230 (DIN VDE 0683-100), threaded T pin shaft DIN 48087 |
| Temperature range | -25 °C ... +55 °C |
| Material (pressure plate) | Aluminium alloy |
| Material (clamp body) | Aluminium alloy |
| Material (shaft) | StSt |
| Weight | 872 g |
| Customs tariff number | 85389099 |
| GTIN | 4013364018686 |
| PU | 1 Stk |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

The clamps must be designed for the same maximum short-circuit current as the earthing and short-circuiting cables!