

Leo CCT



- Modern styled bollard with polycarbonate construction suitable for residential and hospitality applications
- White reflector with clear polycarbonate diffuser
- Polycarbonate construction is ideal for coastal applications
- Supplied c/w root mounting kit, can be surface mounted with rawbolts
- CCT selectable between 3000K and 4000K
- Non-dimmable
- Powered by Tridonic



| INPUT | HERTZ | TEMP | LIFETIME (HRS) | CRI | SDCM | BEAM ANGLE | CLASS | IP | IK |
|-------|---------|-------------|----------------|-------|------|------------|-------|------|------|
| 230V | 50/60Hz | -10 to 40°C | L70 61,000 | Ra 80 | 6 | 130° | 2 | IP65 | IK08 |

| CODE | DESCRIPTION | WATTAGE | CCT | LUMENS | LM/W | A | TRADE |
|--------------------|-------------------------|---------|------------|---------------|--------------|--------|---------|
| ALEOLED/CCT/045/GR | CCT Selectable - 450mm | 8W | | 592lm (4000K) | 74lm (4000K) | 450mm | £135.00 |
| ALEOLED/CCT/075/GR | CCT Selectable - 750mm | 12W | 3000/4000K | 940lm (4000K) | 76lm (4000K) | 750mm | £167.00 |
| ALEOLED/CCT/100/GR | CCT Selectable - 1000mm | | | | | 1000mm | £189.00 |

