

## SPG DCA IT LRM (767 122)

- Nominal voltages up to 45 kV / 50 Hz (three-phase systems)
- Indication by two separate LEDs
- Automatic deactivation



Figure without obligation




Figure without obligation

| Type                              | SPG DCA IT LRM  |
|-----------------------------------|---|
| Part No.                          | 767 122   |
| Nominal voltage (U <sub>n</sub> ) | 1 ... 45 kV   |
| Frequency                         | 50 Hz   |
| Dimensions                        | 120 x 60 x 25 mm  |
| Plug spacing                      | 14 mm   |
| Type of plug                      | 2 multilam plugs (Ø4 mm)                                  |
| Input impedance (LRM system)      | 2 MOhms   |
| Test threshold                    | 3.2 µA  |
| Standard                          | EN/IEC 61243-5 (DIN VDE 0682-415)                         |
| Temperature range                 | -25 °C ... +55 °C   |
| Type of device                    | Interface test unit                                       |
| Use                               | Active indicator for maintenance test of coupling systems |
| Indication                        | Visual  |
| Type of system                    | LRM   |
| Self-testing element              | Yes   |
| Weight                            | 185 g   |
| Customs tariff number             | 90303320  |
| GTIN                              | 4013364074385   |
| PU                                | 1 Stk   |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.