

# PRODUCT DATASHEET DULUX D-E 26W-840 G24Q-3 10X1 RU OSRAM

OSRAM DULUX® D/E | CFLni, 2 tubes, with 4-pin base for ECG operation



#### Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

#### **Product benefits**

- Improved maintenance

#### **Product features**

- Good color rendering index
- Dimmable (3...100 %)
- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in G24q base



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	26 W
Construction wattage	26.90 W
Nominal voltage	105 V
Nominal current	0.33 A

# Photometrical data

Luminous flux	1750 lm
Luminous efficacy	67 lm/W
Color temperature	4000 K
Color rendering index Ra	≥80
Light color	840
Rated LLMF at 2,000 h	0.90
Rated LLMF at 4,000 h	0.84
Rated LLMF at 6,000 h	0.83
Rated LLMF at 8,000 h	0.81
Rated LLMF at 12,000 h	0.79
Rated LLMF at 16,000 h	0.78
Rated LLMF at 20,000 h	0.77

# **Dimensions & Weight**

Overall length	164.50 mm
Diameter	12.00 mm
Product weight	41.5 g

# Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.99
Rated lamp survival factor at 12,000 h	0.95
Rated lamp survival factor at 16,000	0.81
Rated lamp survival factor at 20,000 h	0.50

# Additional product data

Base (standard designation)	G24q-3
Mercury content	1.6 mg

#### **Capabilities**

Dim	nmable	Yes

#### Certificates & Standards

Energy efficiency class	G
Energy consumption	27.00 kWh/1000h

#### **Country-specific categorizations**

Order reference	DULUX D/E 26W/8

# Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G24q-3
Correlated colour temperature type	SINGLE_VALUE
Length	164.50 mm
Height	12.00 mm
Width	12.00 mm
EPREL ID	546451
Model number	AC34226

### **EQUIPMENT / ACCESSORIES**

- Suitable for operation on electronic control gear

#### Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

#### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854122453	Folding box 1	36 mm x 52 mm x 179 mm	56.00 g	0.33 dm <sup>3</sup>
4099854122460	Shipping box 10	187 mm x 81 mm x 196 mm	560.00 g	2.97 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

**OSRAM**