


PRODUCT DATASHEET

FLOOR HOME OFFICE 43W 830 WT EU PLUG

FLOOR STANDING HOME OFFICE | Floor-standing luminaires for home office applications



Areas of application

- Home offices

Product benefits

- Functional LEDVANCE SCALE design
- High light uniformity and low glare light thanks to diffuser
- Energy saving
- Easy to install
- Plug-and-Play due to EU or CH plug
- 5 years guarantee

Product features

- Aluminium housing
- Stand-alone luminaires with direct (25 %) and indirect (75 %) light emission
- Direct/Indirect light controlled together
- Lifetime (L70/B50): 60,000 h (at 25 °C)



TECHNICAL DATA

Electrical data

Nominal wattage	43.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	55 mA
Inrush current	49 A
Inrush current time T_{h50}	304 μ s
Max. no. of lum. on circuit break. B16 A	28
Max. no. of lum. on circuit break. C10 A	30
Max. no. of lum. on circuit break. C16 A	46
Power factor λ	0.95
Total harmonic distortion	< 20 %
Protection class	I
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	5400 lm ¹⁾
Luminous efficacy	126 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥ 80
Standard deviation of color matching	< 3 sdc _m
Low flicker	Yes
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG1
Beam angle	60 ° x 35 °
UGR	≤ 23

¹⁾ Direct luminous flux 1800 lm / Indirect luminous flux 3600 lm

Dimensions & Weight

Length	830.00 mm
Width	400.00 mm

Height	1950.00 mm
Product weight	19100.00 g
Cable length	1500 mm

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polycarbonate (PC)
Light emitting surface material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	0...+35 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Protection class IK (shock resistance)	IK03
Dimmable	Yes
Type of dimming	Push DIM
Mounting type	Standing
Mounting location	Floor
Application environment	Indoor
Adjustable	No
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	60000 h
Lifespan L80/B10 at 25 °C	50000 h
Lifespan L90/B10 at 25 °C	35000 h
Number of switching cycles	50000

Control gear

Output current	1050 mA
ECG - Output ripple current	< 5 %

Certificates & Standards




Standards	CE
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Additional product data





Number of illuminants	-
-----------------------	---

DOWNLOAD DATA

Documents and certificates

	User instruction
	Addon Technical Information
	Declarations Of Conformity CE

Photometric and lighting design files

	IES file (IES)
	LDT file (Eulumdat)
	ULD file (DIALux)
	ROLF file (RELUX)

CAD/BIM files

	CAD_STEP_3D
--	-------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075549883	Shipping box 1	1,180 mm x 430 mm x 277 mm	21412.00 g	140.55 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.