

PRODUCT-DETAILS

DS202 A-K63/0.03

DS202 A-K63/0.03 Residual Current Circuit Breaker with Overcurrent Protection



Algemene informatie

Type	DS202 A-K63/0.03
Artikelnummer	2CSR252101R1637
EAN	8012542931102
Omschrijving	DS202 A-K63/0.03 Residual Current Circuit Breaker with Overcurrent Protection
Omschrijving	The RCBOs DS200 series has the function to protect against overload and short-circuit currents; protection against the effects of sinusoidal alternating earth fault currents; protection against indirect contacts and additional protection against direct contacts.

Technical

Normen	IEC/EN 60947-2 IEC/EN 61009-1
Uitschakelkenmerk	K
Type reststroom	A type
Toegekende spanning (U_r)	230 V AC
Nominaal bedrijfsvoltage	230 V AC
Toegekende stroom (I_n)	63 A
Nominale resterende stroom	30 mA

Nominaal kortsluitvermogen	6 kA
Nominaal ultiem kortsluitvermogen (I_{cu})	(400 V AC) 10 kA
Maximale breekcapaciteit	6 kA
Toegekende frequentie (f)	50 ... 60 Hz
Vermogensverlies	18.2 W
Aansluiting voeding	Arbitrary
Elektrisch uithoudingsvermogen	10000 cycle
Aantal polen	2
Aantal beveiligde polen	2
Aantal aardleautomaten	1
Bedieningskenmerk	Instantaneous
Positie van neutrale klemmen	Right Left
Uitgavetype	K
Opties	None
Accessoires beschikbaar	Yes
Verbindingscapaciteit	Busbar 10 mm ² Rigid 25 ... 25 mm ² Flexible 25 ... 25 mm ²

Environmental

Omgevingsluchttemperatuur	Werking -25 ... +55 °C Opslag -40 ... +70 °C
Weerstand tegen trillingen volgens IEC 60068-2-6	0.1 mm or 1 g - 20 cycles at 5...150...5 Hz
Schokweerstand volgens IEC 60068-2-27	25g 2 shocks 13 ms
RoHS-status	Following EU Directive 2011/65/EU
RoHS-informatie	9AKK106713A5607
REACH-verklaring	9AKK108467A9482
Milieu-informatie	Refer to RoHS
Rapport over conflictmineralen (CMRT)	9AKK108468A3363

Dimensions

Product netto breedte	70 mm
Product netto hoogte	0.093 m
Product netto diepte	69 mm
Product netto gewicht	0.440 kg

Ordering

Minimale bestelhoeveelheid	1 stuk
----------------------------	--------

Pakketniveau 1 Units	doos 1 stuk
Pakketniveau 1 Brutogewicht	0.48 kg

Certificates and Declarations

Conformiteitsverklaring - CE	9AKK106713A5607
---------------------------------	-----------------

Installation

Instructies en handleidingen	9AKK107045A1451
---------------------------------	-----------------

Popular Downloads

Gegevensblad, technische informatie	9AKK107991A8329
--	-----------------

Classifications

ETIM 8	EC002281 - Inbouwwunit met aardlekautomaten
ETIM 9	EC002281 - Inbouwwunit met aardlekautomaten
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
AEEA B2C / B2B	Business To Consumer
CN8	85389099
eClass	V11.0 : 27400618
Object classificatiecode	F

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200909R0001	S2C-A1 Shunt Trip	S2C-A1	1	piece
2CDS200909R0002	S2C-A2 Shunt Trip	S2C-A2	1	piece
2CDS200912R0001	S2C-H6R Auxiliary Contact	S2C-H6R	1	piece
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CDS200946R0001	S2C-H6-11R Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0002	S2C-H6-20R Auxiliary Contact	S2C-H6-20R	1	piece
2CDS200946R0003	S2C-H6-02R Auxiliary Contact	S2C-H6-02R	1	piece
2CSS200911R0002	S2C-UA 24 AC Undervoltage release	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC Undervoltage release	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC Undervoltage release	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC Undervoltage release	S2C-UA 230 AC	1	piece
2CSS200998R0001	S2C-BP Mechanical tripping device	S2C-BP	1	piece

Categorieën

Laagspanningsproducten en -systemen → Modulaire DIN rail producten → Aardlekschakelaars RCD's → Aardlekschakelaars met bescherming tegen overbelasting, RCBO

