


# Osprey High Rack Cold Store Bulkhead



- Modern slim profile IP65 LED polycarbonate bulkhead
- Compact high polished reflector design to provide required light level from high mounting heights
- High performance LED's and optical performance allows increased spacing ratios
- Cold store option incorporates an intelligent integral heat management system to operate in cold store applications down to -30°C
- Self-test as standard
- Aesthetically designed for modern appearance
- 20mm side and rear cable entries



| ***                 | Escape route 2 metres wide (1 Lux minimum) * |                          |               |                |
|---------------------|--|--------------------------|---------------|----------------|
|                     | Transverse to Wall                           | Transverse to Transverse | Axial to Wall | Axial to Axial |
| Mounting Height (M) |  |                          |               |                |
| 10                  | -  | -                        | 4.5           | 20             |
| 15                  | -  | -                        | 1.6           | 14.5           |

| ***                 | Open (Anti-Panic) area (0.5 Lux Minimum)** |                          |               |                |
|---------------------|--|--------------------------|---------------|----------------|
|                     | Transverse to Wall                         | Transverse to Transverse | Axial to Wall | Axial to Axial |
| Mounting Height (M) |  |                          |               |                |
| 10                  | 5.2  | 14                       | 5.2           | 14             |
| 15                  | 5.2  | 17                       | 5.2           | 17             |

| INPUT | HERTZ | TEMP         | LIFETIME (HRS) | BEAM ANGLE | CLASS | IP   | IK   |
|-------|-------|--------------|----------------|------------|-------|------|------|
| 230V  | 50Hz  | -30°C to 5°C | L70 50,000     | 60°x100°   | 1     | IP65 | IK08 |

| CODE         | DESCRIPTION                              | WATTAGE | CCT   | STANDARD MODE | EMERGENCY MODE | TRADE  |
|--------------|--|---------|-------|---------------|----------------|--------|
| AOSLED/3M/CS | Maintained / Non-Maintained - Cold Store | 22W     | 6500K | 445lm         | 354lm          | £95.00 |

| CODE (ACCESSORIES) | DESCRIPTION  | TRADE  |
|--------------------|--|--------|
| ASBP/16            | 4.8V 4Ah Ni-Cd Replacement Battery (for use with Cold Store fitting) | £23.10 |