

PRODUCT DATASHEET

SMART+ ZB PLUG UK

SMART+ Plug | Plug with smart socket to control non smart devices with ZigBee technology



Areas of application

- Wherever non-smart devices need to be integrated into compatible smart home systems

Product benefits

- Integrates conventional electric equipment into compatible smart home systems
- Enables switching of conventional light sources and other electric devices
- Simple connection of electric devices via standard socket

Product features

- Control via compatible smart home system or on/off button on the device
- Control via voice control available: Google Assistant or Amazon Alexa, depending on the smart home system in use
- Network protocol: ZigBee 3.0
- Scheduling
- For full functionality, connection to a compatible smart home System (gateway and app) required
- High switching power up to 3,680W / 16A EU version and 2,990W / 13A UK version



TECHNICAL DATA

Electrical data

Nominal voltage	230 V
Mains frequency	50 Hz

Dimensions & Weight



Product weight	80.00 g
Length	64 mm
Width	55 mm
Height	55 mm

Lifespan

Number of switching cycles	100000
----------------------------	--------

Colors & materials

Product color	White
Body material	Plastic

Temperatures & operating conditions

Ambient temperature range	-20...40 °C
---------------------------	-------------

Capabilities

Compatible smart home technology	Amazon Alexa / Google Assistant / Philips Hue
----------------------------------	---

Certificates & Standards

Protection class	I
Type of protection	IP20




EQUIPMENT / ACCESSORIES

- Control via app requires a compatible Smart home system
-

Safety advice

- Disconnect devices which generate heat from the mains, i.e. from the SMART+ Plug, after use in order to avoid them being accidentally switched on.
- Very high capacitive and inductive loads may in some cases lead to destruction of the device or reduction in the number of switching cycles.
- Do not use the SMART+ Plug in conjunction with medical equipment.
- To be connected to an automatic circuit breaker (max. 13 A).

DOWNLOAD DATA

Documents and certificates	
	Installation guide
	Declarations Of Conformity CE
	Declarations Of Conformity UKCA

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075729285	Folding box 1	61 mm x 96 mm x 154 mm	169.00 g	0.90 dm ³
4058075729292	Shipping box 4	211 mm x 167 mm x 141 mm	796.00 g	4.97 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.