

PRODUCT-DETAILS

XT2N 160 TMG 50-200 4p F F

XT2N 160 TMG 50-200 4p F F



**General Information**

|                       |  |
|-----------------------|--|
| Extended Product Type | XT2N 160 TMG 50-200 4p F F   |
| Product ID            | 1SDA067732R1   |
| EAN                   | 8015644016289  |
| Catalog Description   | XT2N 160 TMG 50-200 4p F F   |
| Long Description      | C.BREAKER TMGX XT2N 160 FIXED FOUR-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMG R 50-200 A |

**ABB EcoSolutions**

|                  |     |
|------------------|-----|
| ABB EcoSolutions | Yes |
|------------------|-----|

**Circular Value**

|   |   |
|---|---|
| Circular Design Principles<br>Recyclability Rate  | Design for Closing Resource Loops - Standard EN45555 - 58.1 % |
| Conflict Minerals<br>Reporting Template<br>(CMRT) | 9AKK108467A5658   |
| End of Life Instructions                          | 9AKK108468A2348   |
| Group Waste to Landfill<br>Target                 | UL 2799 Zero Waste To Landfill Validation available           |
| Toxic Substances Control<br>Act - TSCA            | 9AKK108467A8326   |

---

## Eco Transparency

---

|   |                 |
|---|-----------------|
| Environmental Product Declaration - EPD | 9AKK108468A1891 |
|---|-----------------|

---



---

## Environmental

---

|                           |  |
|---------------------------|--|
| Environmental Information | 9AKK107991A8215<br>9AKK108467A6707                                     |
| REACH Declaration         | 9AKK108466A1425  |
| RoHS Information          | 9AKK108466A1424  |
| RoHS Status               | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

---



---

## Ordering

---

|                          |                    |
|--------------------------|--------------------|
| Order Code US and Canada | XT2NE4050NFF000XXX |
| EAN                      | 8015644016289      |
| Minimum Order Quantity   | 1 piece            |
| Customs Tariff Number    | 85362090           |

---



---

## Dimensions

---

|                            |         |
|----------------------------|---------|
| Product Net Width          | 120 mm  |
| Product Net Height         | 130 mm  |
| Product Net Depth / Length | 82.5 mm |
| Product Net Weight         | 1.45 kg |

---



---

## Container Information

---

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | box 1 piece   |
| Package Level 1 Width          | 131 mm        |
| Package Level 1 Height         | 212 mm        |
| Package Level 1 Depth / Length | 147 mm        |
| Package Level 1 Gross Weight   | 1.55 kg       |
| Package Level 1 EAN            | 8015644016289 |

---



---

## Additional Information

---

|                                       |   |
|---------------------------------------|---|
| Circuit Breaker Type to be Associated | Generator Protection                          |
| Connecting Capacity Main Circuit      | Busbar 32.5..100 mm <sup>2</sup>              |
| Current Type                          | AC/DC   |
| Electrical Durability                 | 120 cycles per hour<br>8000 cycle             |
| Mechanical Durability                 | 240 cycles per hour<br>25000 cycle            |
| Number of Poles                       | 4   |
| Opening Time                          | CB with SOR 15 ms<br>CB with UVR 15 ms        |
| Order Multiple                        | 1 piece                                       |
| Power Loss                            | at Rated Operating Conditions per Pole 4.09 W |
| Product Main Type                     | SACE Tmax XT                                  |
| Product Name                          | Moulded Case Circuit Breaker                  |
| Product Type                          | Automatic Circuit Breaker                     |
| Rated Current (I <sub>n</sub> )       | 50 A  |

---

|   |  |
|---|--|
| Rated Frequency (f)   | 50 / 60 Hz   |
| Rated Voltage ( $U_r$ )                                     | 690 V  |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 8 kV   |
| Rated Instantaneous Short-Circuit Current Setting ( $I_s$ ) | 200 A  |
| Rated Insulation Voltage ( $U_i$ )                          | 1000 V   |
| Rated Operational Voltage                                   | 690 V AC<br>500 V DC   |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (220 V AC) 65 kA<br>(230 V AC) 65 kA<br>(240 V AC) 65 kA<br>(380 V AC) 36 kA<br>(415 V AC) 36 kA<br>(440 V AC) 36 kA<br>(500 V AC) 30 kA<br>(525 V AC) 20 kA<br>(690 V AC) 10 kA<br>(250 V DC) 2 Poles in Series 36 kA<br>(500 V DC) 3 Poles in Series 36 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ) | (220 V AC) 65 kA<br>(230 V AC) 65 kA<br>(240 V AC) 65 kA<br>(380 V AC) 36 kA<br>(415 V AC) 36 kA<br>(440 V AC) 36 kA<br>(500 V AC) 30 kA<br>(525 V AC) 20 kA<br>(690 V AC) 10 kA<br>(250 V DC) 2 Poles in Series 36 kA<br>(500 V DC) 3 Poles in Series 36 kA |
| Rated Uninterrupted Current ( $I_u$ )                       | 160 A  |
| Recommended Screw Driver                                    | Main Circuit M6  |
| Release   | TMG  |
| Release Type  | TM   |
| Setting Range   | 35...50 A  |
| Short-Circuit Performance Level                             | N  |
| Standards   | IEC  |
| Sub-type  | XT2  |
| Terminal Connection Type                                    | Front  |
| Terminal Type   | Bolt   |
| Tightening Torque   | 6 N·m  |
| Version   | F  |
| CAD Dimensional Drawing                                     | 1SDH002230A1002  |

### Certificates and Declarations

|                                   |                                    |
|-----------------------------------|------------------------------------|
| ATEX Certificate                  | No certification needed            |
| Data Sheet, Technical Information | 1SDC210100D0206<br>1SDC210099D0206 |
| Declaration of Conformity - CE    | 9AKK106713A5901                    |
| GL Certificate                    | 1SDL000163R0093                    |
| LR Certificate                    | 1SDL000163R0100                    |
| UL Certificate                    | No certification needed            |
| VDE Certificate                   | No certification needed            |
| Dimension Diagram                 | 1SDH000721R0100                    |
| Mechanical Drawings               | 1SDH000721R0100                    |
| Wiring Diagram                    | 1SDM000068R0001                    |
| Instructions and Manuals          | 1SDH000721R0001                    |

---

## Classifications

|                            |  |
|----------------------------|--|
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 8                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| ETIM 9                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q  |
| UNSPSC                     | 39120000   |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |
| eClass                     | V11.1 : 27370409   |

---

## Categories

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

