Product Data Sheet

GW68494

68 ACS Range



The distribution board for construction sites type Q-BOX are designed to withstand the effects of wear, impact and the stress caused by atmosph. They come in pre-wired versions fitted with interlocked socketoutlets (with or without a fuse-holder) up to 63A, or socket-outlets type IEC 309.. The wired versions are also equipped with accessories like the emergency push-button, lockable doors, stainless steel tear-proof cablefastening hooks, and built-in transportation handles on the upper part of the board. To ensure the best possible positioning on the construction site, 68 Q-BOX ACS boards can be surface-mounted, floor-mounted or fitted on poles.

Туре	Q-BOX 6 ACS	board type	Wired		
Colour	Light blue	Outer dim. LxHxD (mm)	914x821x400		
Weight (kg)	30	Accordance with Standards	EN 61439-4 (ACS)		
Characteristics	UV resistance (EN 62208)	IP degree	IP55		
Mechanical resistance	IK10	Glow wire test	650 °C		
Thermo-pressure with ball	70 °C	Insulation class	II		
Power supply	Terminal block	No. of poles	3P+N+E		
Power suppliable (kW)	33	Mains switch	MCB 63A 4P 6kA		
MCB'S MT main RCCB	RCCB 63A 4P 0,03A - AC type	Circuits protection	MCB		
No. socket outlets	6	Socket-outlet 2P+E 16A - IB	2		
Socket-outlet 3P+E 16A - IB	2	Socket-out 3P+E 32A - IB	2		
Emergency push-button	Yes	Electrocod	139		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS												
Saline solution	Acids		Bases		Solvents			Mineral	UV			
	Concentrated	Diluited	Concentrated	Diluited	Hexane	Benzol	Acetone	Ethyl alcohol	oil	rays		
Resistant	Limited resistance	Resistant	Limited resistance	Resistant	L <mark>imite</mark> d resistance	L <mark>imite</mark> d resistance	L <mark>imited</mark> resistance	Resistant	L <mark>imite</mark> d res <mark>ista</mark> nce	Resistant		

DIMENSIONAL

TECHNICAL SYMBOLOGY

















STANDARDS/APPROVALS

