



# CoreLine Highbay Gen5

## BY120P G5 LED105S/840 PSU NB

- Power supply unit (ON/OFF) - Beam angle 55° - 55°

CoreLine Highbay Gen5 delivers on the CoreLine promise of innovative, easy-to-use and high-quality luminaires. A reliable, highly-efficient luminaire with a very long-lifetime, it delivers great energy savings and requires less maintenance. At the same time, CoreLine Highbay is very easy to handle. The luminaire can be installed on your existing grid and the electrical connection is a straightforward task, with no need to open the luminaire and an external IP65 connector. With a choice of two beam angles: narrow and wide beam, you can adjust your lighting plan to suit your exact needs. This range also includes Interact Ready luminaires with integrated wireless communications and integrated movement and daylight sensors. So CoreLine Highbay Gen5 is ready to be used with any Interact connected lighting system.

### Product data

General Information		Flickering value (PstLM)		0.5	
Light source replaceable	No	Stroboscopic effect value (SVM)	1		
Number of gear units	1 unit	Light source color	840 neutral white		
Driver included	Yes	Optic type	Beam angle 55°		
Lighting Technology	LED	Luminaire light beam spread	55°		
		Unified glare rating CEN	22		
Light Technical		Operating and Electrical			
Luminous Flux	10,500 lumen	Input Voltage	220 to 240 V		
Saturated Red (R9)	<50	Line Frequency	50 or 60 Hz		
Luminous Efficacy (rated) (Nom)	157 lm/W	Input Frequency	50 or 60 Hz		
Color rendering index (CRI)	>80				

# CoreLine Highbay Gen5

Power Consumption	67 W
Inrush current	40 A
Inrush time	600 ms
Power Factor (Fraction)	0.95
Connection	Connection unit 3-pole
Cable	Cable 0.3 m with connector 3-pole
Number of products on MCB of 16 A type B	6

## Temperature

Ambient temperature range	-30 to +50 °C
---------------------------	---------------

## Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (ON/OFF)
Control interface	-
Constant light output	No

## Mechanical and Housing

Housing Material	Aluminum die-cast
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	-
Housing Color	Dark gray
Optical cover/lens finish	Clear
Overall height	90 mm
Overall diameter	290 mm

## Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Sustainability rating	-
Protection class IEC	Safety class I
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	ENEC mark
Warranty period	5 years

Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Photobiological risk specification	18.2 m
EU RoHS compliant	Yes

## Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Init. Corr. Color Temperature	4000 K
Initial chromaticity	(0.385, 0.380) SDCM<5
Power consumption tolerance	+/-10%

## Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance at median useful life* 50000 h	L85
Lumen maintenance at median useful life* 100000 h	L65

## Application Conditions

Performance ambient temperature Tq	35 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes

## Product Data

Full product code	871951495566000
Order product name	BY120P G5 LED105S/840 PSU NB
EAN/UPC - Product	8719514955660
Order code	911401629208
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material number (12NC)	911401629208
Net weight	1.990 kg
Full product name	BY120P G5 LED105S/840 PSU NB
EAN/UPC - Case	8719514955660



# CoreLine Highbay Gen5

## Dimensional drawing

