


SR D50 4700 FS22 2500 IP HVI GFK AL (105 333)



Figure without obligation



Supporting tube with internal sealing end and EB spring element. Air-termination rod $\varnothing 22/16/10$ mm.

| Type | SR D50 4700 FS22 2500 IP HVI GFK AL |
|---|---------------------------------------|
| Part No. | 105 333 |
| Material of air-termination rod | Al |
| Length of air-termination rod | 2500 mm |
| Material of supporting tube | GRP / Al |
| Length of supporting tube | 4700 mm |
| Transport length | 4700 mm |
| Outside diameter \varnothing | 50 mm |
| Length of insulating clearance | 1535 mm |
| Wall thickness | 4 mm |
| Material factor km | 0.7 |
| Permanent temperature range | -50 °C ... +100 °C |
| Type | UV-stabilised |
| Sleeve | 60 x 5 mm |
| Max. free length with air-termination rod (wall mounting) | 5000 mm |
| Max. gust wind speed (wall mounting, 1x HVI inside) | 190 km/h |
| Max. gust wind speed (wall mounting, 1x HVI outside) | 175 km/h |
| Max. gust wind speed (wall mounting, 4x HVI outside) | 163 km/h |
| Standard | DIN IEC/TS 62561-8 (VDE V 0185-561-8) |
| Weight | 8,51 kg |
| Customs tariff number | 85389099 |
| GTIN | 4013364152526 |
| PU | 1 Stk |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.