

WLD+40008_SMART


WLD+40008_SMART



Power	10 W	Voltage	48 V
Colour temperature	3000/4000/6000 K	Colour of light	CCT
Beam angle	100 °	Degree of protection (IP)	IP20


Technical data

Code	WLD+40008_SMART
Power	10 W
Nominal current	210 mA
Voltage	48 V
Energy consumption	10 kWh/1000h
Frequency	DC Hz
Protection class	III
Power factor	1
Useful luminous flux*	940 lm (360°)
Luminous flux**	400 lm (360°)
Lamp efficacy	94 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	100 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Working temperature range	-20 to +40 °
Lifespan	50000 h
Housing material	AL+PC
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	304x23x42 mm
For use	Inside
Assembly method	NA SZYNE
Application	Inside
Made in	PRC
Other	CCT/DIM ,









Related documents



 User manual



 Declaration of Conformity

	<p>48V </p>  <p>Die Montage erfolgt über ein einfaches Klick-System zusätzlich lässt sich die Leuchte je nach Bedarf verschieben</p>	<p>48V </p>  <p>Luminaire assembly within the track on "click" and its free arrangement</p>
---	--	---

