

LIMEA CONNECT

SLI028112NW_PW

Hermetic luminaire LIMEA CONNECT, with a power of 50 W, high light efficacy 154 lm/W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	50 W	Voltage	230 V
Luminous flux*	7700 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
IK	08	Degree of protection (IP)	IP65

Technical data


Code	SLI028112NW_PW
Power	50 W
Nominal current	220 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.98
Useful luminous flux*	7700 lm (360°)
Luminous flux**	6000 lm (360°)
Lamp efficacy	154 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	26000 h
Housing material	PC/PC
IK	08
Degree of protection (IP)	IP65
Colour	Gray
Dimension (AxBxC)	1200x64x60 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 16 pcs per line ,

Related documents



 User manual



 Declaration of Conformity



 Photometric file

