

PRODUCT-DETAILS

S201MT-B20NA

S201MT-B20NA Miniature Circuit Breakers

MCBs - 1+NP - B - 20 A



Informations générales

| | |
|------------------------------|--|
| Extension du type de produit | S201MT-B20NA |
| Code de produit | 2CDS271446R0205 |
| EAN | 4016779122337 |
| Description courte | S201MT-B20NA Miniature Circuit Breakers MCBs - 1+NP - B - 20 A |
| Description longue | S201MT-B20NA Miniature Circuit Breaker B-Char., 10kA, 20A, 1P, +NA |

Technique

| | |
|--|---|
| Normes et standards | IEC/EN 60898-1, IEC/EN 60947-2, UL 1077, CSA 22.2 No. 235 |
| Tripping Characteristic | B |
| Tension nominale (U_p) | 440 V |
| Tension | acc. to IEC 60898-1 400 V acc. to IEC 60947-2 230 V |
| Operational Voltage | Maximum (Incl. Tolerance) 253 V AC Maximum (Incl. Tolerance) 66 V DC Minimum 12 V AC Minimum 12 V DC |
| Tension assignée d'isolement (U_i) | acc. to IEC/EN 60664-1 440 V |
| Tension assignée de | 4 kV |

| | |
|---|---|
| tenue aux chocs (U_{imp}) | at 2000 m 5 kV at Sea Level 6.2 kV |
| Dielectric Test Voltage | 50/60 Hz, 1 min: 2 kV |
| Type de tension | AC |
| Courant nominal (I_n) | 20 A |
| Rated Short-Circuit Capacity | 10 kA |
| Pouvoir assigné de coupure ultime en court-circuit (I_{cu}) | 15 kA (230 V) 15 kA (400 V) 15 kA |
| Pouvoir assigné de coupure de service en court-circuit (I_{cs}) | 11.2 kA |
| Fréquence assignée (f) | 50 / 60 Hz |
| Power Loss | 5 W |
| Classe de limitation d'énergie | 3 |
| Mechanical Endurance | 20000 cycle |
| Nombre de pôles | 1+N |
| Number of Protected Poles | 1 |
| Catégorie de Surtension | III |
| Couple de serrage | 2.8 N·m |
| Screw Terminal Type | Failsafe Bi-directional Cylinder-lift Terminal |
| Actuator Marking | I / O |
| Actuator Material | Insulation Group II, Black, Sealable |
| Qualité du matériau | Insulation Group I, RAL 7035 |
| Montage sur rail DIN | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Type d'encastrement | any |
| Recommended Screw Driver | Pozidriv 2 |
| Accessories Available | Oui |
| Connecting Capacity | Busbar 10 / 10 mm ² Flexible with Ferrule 0.75 ... 16 mm ² Flexible 0.75 ... 25 mm ² Stranded 0.75 ... 35 mm ² |
| Installation Size | acc. to DIN 43880 3 |
| Type de borne | Screw Terminals |

Environnement

| | |
|--|---|
| Température de l'air ambiant | Operation -40 ... +70 °C Storage -40 ... 75 °C |
| Indice de protection | Enclosure with Cover IP20 |
| Degré de pollution | 3 |
| Environmental Conditions | 28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 % |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In |

| | |
|--|--|
| Résistance aux chocs selon CEI 60068-2-27 | 25g 2 shocks 13 ms |
| Statut RoHS | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Informations RoHS | 2CQB100288 |
| REACH Declaration | 9AKK107492A1906 |

Dimensions

| | |
|--|----------|
| Produit Largeur Net | 35 mm |
| Produit Hauteur Net | 88 mm |
| Produit Longueur Net | 69 mm |
| Poids net | 0.25 kg |
| Pole Net Weight | 0.115 kg |
| Profondeur d'encastrement (t ₂) | 69 mm |

Commande

| | |
|------------------------------|-------------|
| Quantité minimum | 1 pièce |
| Emballage Niveau 1 Unités | box 5 pièce |
| Emballage Niveau 1 Poids | 1.262 kg |

Certificats et Déclarations (Numéro de document)

| | |
|-----------------------------------|------------|
| Agence de certification | EN IEC |
| Déclaration de Conformité - CE | 2CQB100288 |

Installation

| | |
|-------------------------|-----------------|
| Instructions et manuels | 2CDS207104P0002 |
|-------------------------|-----------------|

Popular Downloads

| | |
|---|-----------------|
| Fiche produit, informations techniques | 9AKK108467A7598 |
|---|-----------------|

Classifications

| | |
|----------------|--|
| ETIM 8 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 9 | EC000042 - Miniature circuit breaker (MCB) |
| Catégorie DEEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| DEEE B2C / B2B | Business To Business |
| CN8 | 8536 20 10 |
| UNSPSC | 39121603 |

eClass

V11.0 : 27141901

Code de catégorie
granulaire IDEA (IGCC)

4897 >> Miniature circuit breakers

Code de classification
d'objet

F

Accessories

| Identifiant | Description | Type | Quantity | Unit Of Measure |
|-----------------|--------------------------------------|---------------|----------|-----------------|
| 2CDS200922R0001 | S2C-S/H6R Signal / Auxiliary Contact | S2C-S/H6R | 1 | piece |
| 2CDS200912R0001 | S2C-H6R Auxiliary Contact | S2C-H6R | 1 | piece |
| 2CDS200936R0001 | S2C-H11L Auxiliary Contact | S2C-H11L | 1 | piece |
| 2CDS200936R0002 | S2C-H20L Auxiliary Contact | S2C-H20L | 1 | piece |
| 2CDS200936R0003 | S2C-H02L Auxiliary Contact | S2C-H02L | 1 | piece |
| 2CDS200946R0001 | S2C-H6-11R Auxiliary Contact | S2C-H6-11R | 1 | piece |
| 2CDS200946R0002 | S2C-H6-20R Auxiliary Contact | S2C-H6-20R | 1 | piece |
| 2CDS200946R0003 | S2C-H6-02R Auxiliary Contact | S2C-H6-02R | 1 | piece |
| 2CDS200909R0001 | S2C-A1 Shunt Trip | S2C-A1 | 1 | piece |
| 2CDS200909R0002 | S2C-A2 Shunt Trip | S2C-A2 | 1 | piece |
| 2CSS200911R0001 | S2C-UA 12 DC Undervoltage release | S2C-UA 12 DC | 1 | piece |
| 2CSS200911R0002 | S2C-UA 24 AC Undervoltage release | S2C-UA 24 AC | 1 | piece |
| 2CSS200911R0003 | S2C-UA 48 AC Undervoltage release | S2C-UA 48 AC | 1 | piece |
| 2CSS200911R0004 | S2C-UA 110 AC Undervoltage release | S2C-UA 110 AC | 1 | piece |
| 2CSS200911R0005 | S2C-UA 230 AC Undervoltage release | S2C-UA 230 AC | 1 | piece |
| 2CSS200911R0006 | S2C-UA 400 AC Undervoltage release | S2C-UA 400 AC | 1 | piece |
| 2CSS200911R0007 | S2C-UA 24 DC Undervoltage release | S2C-UA 24 DC | 1 | piece |
| 2CSS200911R0008 | S2C-UA 48 DC Undervoltage release | S2C-UA 48 DC | 1 | piece |
| 2CSS200911R0009 | S2C-UA 110 DC Undervoltage release | S2C-UA 110 DC | 1 | piece |
| 2CSS200911R0010 | S2C-UA 230 DC Undervoltage release | S2C-UA 230 DC | 1 | piece |
| 2CSS201997R0013 | S2C-CM1 Motor operating device | S2C-CM1 | 1 | piece |
| 2CSS203997R0013 | S2C-CM2/3 Motor operating device | S2C-CM2/3 | 1 | piece |
| 2CSS204997R0013 | S2C-CM4 Motor operating device | S2C-CM4 | 1 | piece |
| GHS2001901R0003 | S2C-DH Mechanical Accessories | S2C-DH | 1 | piece |
| 2CSS200998R0001 | S2C-BP Mechanical tripping device | S2C-BP | 1 | piece |
| 2CSS200999R0001 | S2C-EST Plug-in base | S2C-EST | 1 | piece |
| 2CDS200918R0001 | S2C-NT Hand Operated Neutral | S2C-NT | 1 | piece |
| 2CCA880100R0001 | CMS-100PS Sensor | CMS-100PS | 1 | piece |
| 2CCA880101R0001 | CMS-101PS Sensor | CMS-101PS | 1 | piece |
| 2CCA880102R0001 | CMS-102PS Sensor | CMS-102PS | 1 | piece |

Catégories

Produits basse tension → Appareillage modulaire et parafoudres → Miniature Circuit Breakers MCBs → Disjoncteurs ≤63A SN201/S200

