

# PRODUCT DATASHEET

## STERIWHITE AIRQ115 W

STERIWHITE AIRQ115 | UVC disinfection of ambient air in rooms with constant occupancy



---

### Product features

- Extremely quiet, no annoying air flow
- Energy-efficient
- Low-maintenance
- Easy operation
- Modern design
- One performance level 115 m<sup>3</sup>/h at <35 dB (A)
- Made in Germany

**TECHNICAL DATA**

**Electrical data**

Nominal wattage	60.00 W
Nominal voltage	230 V
Mains frequency	50 Hz
Protection class	I
Operating mode	Integrated driver


**UV & Air cleaning**

Maximum disinfection volume flow	115 m <sup>3</sup> /h
Air circulation	115 m <sup>3</sup> /h
UV radiated power	46 W
UV-C source lifetime	16000 h
Noise level in UV-C disinfection mode	< 35 dB
Suitable for room space up to	25 m <sup>2</sup>

**Dimensions & Weight**

Length	100.00 mm <sup>1)</sup>
Width	600.00 mm <sup>1)</sup>
Height	600.00 mm <sup>1)</sup>
Product weight	17000.00 g
Cable length	3000 mm

<sup>1)</sup> The dimension can vary depending on type of mounting variant



**Materials & Colors**

Product color	White
Body material	Steel

Mercury content	0.0 mg
-----------------	--------

### Application & Mounting

Ambient temperature range	0...+40 °C
Type of connection	Plug type C (EU)
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Wall / Ceiling

### Certificates & Standards

Standards	CE
-----------	----

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4260732190011	Shipping box 1	700 mm x 700 mm x 200 mm	21000.00 g	98.00 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.