


## D BEB 0 - 70 / EBS 15-03-19 (419 001)



Figure without obligation



### Stainless steel earthing bridges

The earthing bridges are designed for earthing, current return circuits and equipotential bonding in railway line applications. The stainless steel earthing bridge ensures this via a defined welding seam to the earthing conductor. This earthing bridge also has a technical approval from DB Netz AG and can be reliably used in planning.

Type	D BEB 0 - 70 / EBS 15-03-19
Part No.	419 001 <b>NEW</b>
Material of connection element	StSt
Material No.	1.4301
Short-circuit current	> 25 kA
Test current	40 kA / 100 ms
Standard	Ril 997.0205A01
Short-circuit current (AC 50 Hz / DC) (1 s; ≤ 300°C)	12.6 kA
Thread	M16
Diameter of connection plate	50 mm
Total height	70 mm
Installation height	62 mm
DB drawing No.	3 Ebs 15.03.19 - 37
Weight	950 g
Customs tariff number	85369010
GTIN	4013364439429
PU	1 Stk

Note: The D BEB 0 earthing bridges can be made to order up to a height of 100 mm without losing their DB Netz AG approval.

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.