

# PRODUCT DATASHEET LS AY SUP -CP/P3/500

## Connectors for TW LED Strips | Connectors for TW LED Strips



### Areas of application

- General indoor illumination

#### Product benefits

- Easy installation of connector, no manual wiring required
- Tool-free installation

#### **TECHNICAL DATA**

#### Electrical data

Nominal voltage	036 V
Nominal current	5000 mA

## **Dimensions & Weight**

Length	24.3 mm
Cable length	500 mm
Width	14.6 mm
Height	7.7 mm
Cable cross-section, input side	0.350.75 mm <sup>2</sup>
Product weight	14.00 g

## Colors & materials

Product color	Transparent
---------------	-------------

## Temperatures & operating conditions

Ambient temperature range	-20+55 °C
Temperature range in operation	-20+55 °C

### **Certificates & Standards**

Type of protection	IP00
LOGISTICAL DATA	
Temperature range at storage	-35+85 °C

#### DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	Declarations of conformity	LED STRIP ACCESSORIES	
	Tender texts	Document name	
	Tender documents	Connectors for TW LED Strips CPP3500-EN	

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075451322	BAG 2	80 mm x 120 mm x 5 mm	29.00 g	0.05 dm <sup>3</sup>

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075451339	Shipping box 100	250 mm x 100 mm x 250 mm	1598.00 g	6.25 dm <sup>3</sup>
4058075451346	Shipping box 1,000	520 mm x 520 mm x 270 mm	30042.00 g	73.01 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.