



CorePro LEDspot MV

CorePro LEDspot 3-35W GU10 830 36D DIM

CorePro LEDspots are a perfect fit for spot lighting and deliver warm halogen-like light. These GU10 LED spot lights are compatible with most existing fixtures with a GU10 LED base and are designed as a retrofit replacement for halogen or incandescent spots. CorePro LEDspots deliver significant energy savings and minimize maintenance costs.

Product data

General Information	
Cap-Base	GU10 [GU10]
CE mark	Yes
EU RoHS compliant	Yes
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Narrow Cone
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	36 degree(s)
Luminous Flux	230 lumen
Luminous Intensity (Nom)	500 cd
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Luminous Efficacy (rated) (Nom)	76 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux in 90° Cone (Rated)	230 lumen


Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	3 W
Lamp Current (Nom)	18 mA
Wattage Equivalent	35 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.8
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	65 °C
Controls and Dimming	
Dimmable	Only with specific dimmers
Mechanical and Housing	
Bulb Shape	PAR16 [PAR 2 inch/50mm]
Approval and Application	
Suitable For Accent Lighting	Yes

CorePro LEDspot MV

Energy Consumption kWh/1000 h	3 kWh
EPREL Registration Number	391,910
Product Data	
Full product code	871869672135300
Order product name	CorePro LEDspot 3-35W GU10 830 36D DIM
Order code	929002068202
Numerator - Quantity Per Pack	1



Numerator - Packs per outer box	10
Material number (12NC)	929002068202
Net weight	0.048 kg
Full product name	CorePro LEDspot 3-35W GU10 830 36D DIM
EAN/UPC - Case	8718696721360

Dimensional drawing




Product	D	C
CorePro LEDspot 3-35W GU10 830 36D DIM	50 mm	54 mm

Photometric data




Light Distribution Diagram - CorePro LEDspot 3-35W GU10 830 36D DIM



Spectral Power Distribution Colour - CorePro LEDspot 3-35W GU10 830 36D DIM

CorePro LEDspot MV

Lifetime



Life Expectancy Diagram - CorePro LEDspot 3-35W GU10 830 36D DIM

Lumen Maintenance Diagram - CorePro LEDspot 3-35W GU10 830 36D DIM

