

PRODUCT-DETAILS

# S802C-D10

## S802C-D10 High Performance MCB



### General Information

|                       |                                |
|-----------------------|--------------------------------|
| Extended Product Type | S802C-D10                      |
| Product ID            | 2CCS882001R0101                |
| EAN                   | 7612271212179                  |
| Catalog Description   | S802C-D10 High Performance MCB |

|                  |  |
|------------------|--|
| Long Description | <p>The S802C-D10 is a 2-pole High Performance Circuit breaker with D-Characteristic, with cage terminal and a rated current of 10 A. It is a current limiting device with a maximum breaking capacity of 25kA at 240/415V. It can be used for voltages up to 254/440V and in DC as well. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S802C-D10 complies with IEC/EN 60898-1 and IEC/EN 60947-2 and allows the use for residential, commercial and industrial applications. It has numerous of approvals, therefore it can be used worldwide. The extensive range of accessory makes the use of S802C-D10 more comfortable. Due to the fast arc extinction of S802C-D10 your application will be secured.</p> |
|------------------|--|

### Technical

|                                 |  |
|---------------------------------|--|
| Standards                       | IEC/EN 60947-2, IEC/EN 60898-1, UL 1077  |
| Tripping Characteristic         | D  |
| Rated Voltage (U <sub>r</sub> ) | acc. to IEC 60947-2 440 V AC<br>acc. to IEC 60947-2 250 V DC<br>acc. to IEC 60898-1 400 V AC |

|  |   |
|--|---|
| Rated Operational Voltage  | acc. to IEC 60898-1 400 V   |
| Operational Voltage  | Maximum 230/400 V AC<br>Minimum 12 V AC   |
| Rated Insulation Voltage<br>( $U_i$ )                              | acc. to IEC/EN 60664-1 500 V  |
| Rated Impulse Withstand<br>Voltage ( $U_{imp}$ )                   | 8 kV  |
| Input Voltage Type   | AC/DC   |
| Rated Current ( $I_n$ )  | 10 A  |
| Rated Operational Current<br>( $I_e$ )                             | 10 A  |
| Rated Short-Circuit<br>Capacity                                    | (230 V) 15 kA<br>(400 V) 15 kA  |
| Rated Ultimate Short-<br>Circuit Breaking Capacity<br>( $I_{cu}$ ) | (230 V) 25 kA<br>(400 V) 25 kA  |
| Rated Conditional Short-<br>Circuit Current ( $I_{nc}$ )           | (230 V) 25 kA<br>(400 V) 25 kA  |
| Rated Service Short-<br>Circuit Breaking Capacity<br>( $I_{cs}$ )  | (240 / 415 V AC) 18 kA<br>(254 / 440 V AC) 10 kA<br>(125 V DC) 10 kA  |
| Frequency (f)  | 50 / 60 Hz  |
| Rated Frequency (f)  | 50/60 Hz  |
| Power Loss   | 3 W<br>at Rated Operating Conditions per Pole 1.5 W   |
| Contact Position<br>Indication                                     | ON / OFF / TRIP   |
| Energy Limiting Class  | 3   |
| Electrical Endurance   | 10000 cycle   |
| Mechanical Endurance   | 10000 cycle   |
| Number of Poles  | 2   |
| Number of Protected<br>Poles                                       | 2   |
| Overvoltage Category   | IV  |
| Tightening Torque  | 3.5 N·m<br>31 in·lb   |
| Release Type   | D   |
| Actuator Marking   | I / O   |
| Housing Material   | Insulation group I, RAL 7035  |
| Mounting on DIN Rail   | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715          |
| Mounting Position  | Any   |
| Recommended Screw<br>Driver  | Pozidriv 2  |
| Accessories Available  | Yes   |
| Remarks  | Connection from top and bottom Connecting with CU only IP40 in enclosure<br>with cover Cage terminal with captive screw |
| Connecting Capacity  | Flexible 0 ... 50 mm <sup>2</sup><br>Rigid 0 ... 70 mm <sup>2</sup>   |
| Terminal Type  | Screw Terminals   |

---

**Environmental**


---

|   |   |
|---|---|
| Ambient Temperature                               | -25...60 °C   |
| Ambient Air Temperature                           | Operation -25 ... 60 °C                                   |
| Reference Ambient Air Temperature                 | acc. to IEC60947-2 30 °C<br>acc. to EN60898-1 30 °C       |
| Degree of Protection                              | IP20  |
| Pollution Degree                                  | 3   |
| Resistance to Vibrations<br>acc. to IEC 60068-2-6 | 2 - 13.2 Hz / 1mm 13.2 - 100Hz / 0.7g with load 100% x le |
| Resistance to Shock acc.<br>to IEC 60068-2-27     | 5 g<br>30 ms  |
| RoHS Status                                       | Following EU Directive 2011/65/EU                         |
| RoHS Information                                  | 9AKK107680A3903<br>2CCC005083D0202                        |
| Environmental Information                         | 2CCY413207D0203   |
| Conflict Minerals<br>Reporting Template<br>(CMRT) | 9AKK108468A3363   |

---



---

**Technical UL/CSA**


---

|                                       |   |
|---------------------------------------|---|
| Interrupting Rating acc. to<br>UL1077 | (480Y / 277 V AC) 10 kA<br>(250 V DC) 10 kA |
|---------------------------------------|---|

---



---

**Dimensions**


---

|  |                 |
|--|-----------------|
| Width in Number of<br>Modular Spacings | 3               |
| Product Net Width                      | 54 mm           |
| Product Net Height                     | 95 mm           |
| Product Net Depth /<br>Length          | 82.5 mm         |
| Product Net Weight                     | 490 g           |
| Built-In Depth (t <sub>2</sub> )       | 82.5 mm         |
| Dimension Diagram                      | 2CCC413003C0201 |

---



---

**Ordering**


---

|                                 |             |
|---------------------------------|-------------|
| Minimum Order Quantity          | 1 piece     |
| Package Level 1 Units           | box 1 piece |
| Package Level 1 Gross<br>Weight | 510 g       |

---



---

**Certificates and Declarations**


---

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of Conformity<br>- CE | 2CCC005083D0202 |
|-----------------------------------|-----------------|

---

---

## Installation

---

Instructions and Manuals

2CCC413016M0008

---

## Popular Downloads

---

Data Sheet, Technical  
Information

2CCC413003C0208

---

## Classifications

---

|                            |  |
|----------------------------|--|
| ETIM 8                     | EC000042 - Miniature circuit breaker (MCB)                 |
| ETIM 9                     | EC000042 - Miniature circuit breaker (MCB)                 |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B             | Business To Business                                       |
| CN8                        | 85362020   |
| eClass                     | V11.0 : 27141901   |
| Object Classification Code | F  |

---



---

## Categories

---

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs → High Performance Circuit Breakers HPCBs

