


1 solid state
relay 5-24Vdc/24Vdc 500mA screw, not pluggable

Series	
Code	X766082
Type	CWOT 6-6082 (1)
HS code	85049090
INPUT TECHNICAL DATA	
Input rated voltage	5-12-24 Vdc (range 4.5...28 Vdc)
Pull in / drop out voltage type	4.2 V / 2.7 V
Current consumption	0.1 mA \pm 10%
Turn ON / OFF time	12 μ s / 12 μ s
Frequency	20 KHz
Connection terminal	2.5 mm ² screw
Input channels	1 not pluggable
OUTPUT TECHNICAL DATA	
Contact type	mosfet
Output voltage	5..48 Vdc
Nominal current	10...500 mA (24 Vdc)
Connection type	
GENERAL TECHNICAL DATA	
Operating temperature range	-25...+60°C
Input / output isolation	3.5 kVac / 60 s
Protection degree	IP 20
Overvoltage category / pollution degree	II / 2
Status indication	LED "Input"
Housing material	UL94V-0 plastic material
Dimensions (LxHxD)	6.2x79x84 mm
Approximate weight	29 g
Mounting information	on a rail, side by side
ACCESSORIES	
Mounting rail (IEC60715/TH35-7.5)	PR/3/AC, PR/3/AC/ZB, PR/3/AS, PR/3/AS/ZB
APPROVALS AND MARKINGS	
	CE



* Not-pluggable relay
1 Manufacturer and model of the components is not binding, technical data are to be considered typical2 (1) Version produced upon request; contact our sales office for availability.

DESCRIZIONE DEL PRODOTTO

CWOT6-2082 1 solid state
relay 5-24Vdc/24Vdc 500mA screw, not pluggable