PHILIPS Lighting



CorePro Plastic LEDcandles & lusters

CorePro candle ND 5-40W E14 865 B35 FR

The CorePro LEDcandles and lusters are designed for retrofit replacement of incandescent lamps and are particularly attractive for chandeliers. They are compatible with fixtures with an E14 holder for candles and E14 or E27 holders for lusters and are available in multiple color temperatures. LED lamps deliver huge energy savings of up to 80% energy-saving compared with halogen lamps and provide excellent quality of light. By offering a lifetime of 15,000 hours it lowers maintenance costs. The CorePro LED candles and lusters are perfect for your basic lighting needs.

Product data

General Information	
Cap-Base	E14
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Light Technical	
Color Code	865 [CCT of 6500K]
Luminous Flux	470 lm
Color Designation	Cool Daylight
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	94.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Photobiological safety according to EN 62471	RG1

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	5 W
Lamp Current (Nom)	44 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.51
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	81 °C
Controls and Dimming	
Dimmable	No




CorePro Plastic LEDcandles & lusters

Frosted
B35
0.040 kg
F
5 kWh
453201
Yes
Yes
Yes
1
0.4
No


Product Data	
Order product name	CorePro candle ND 5-40W E14 865
	B35 FR
Full product name	CorePro candle ND 5-40W E14 865
	B35 FR
Full product code	871951431258600
Order code	929002969202
Material Nr. (12NC)	929002969202
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514312586
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514312593

Dimensional drawing



Product	D	С
CorePro candle ND 5-40W E14 865 B35 FR	35 mm	106 mm

Photometric data




		General Uniform Lighting
		1 x 1210021412 SW 4500K
		1.470.00
No may here	Questa reination depun	UGR dagram
Anna Anna A	Uterate later tils	

Spectral Power Distribution Colour - CorePro candle ND 5-40W E14 865 B35 FR


CorePro Plastic LEDcandles & lusters

Photometric data



Light Distribution Diagram - CorePro candle ND 5-40W E14 865 B35 FR

Lifetime



Life Expectancy Diagram

Lumen Maintenance Diagram - CorePro candle ND 5-40W E14 865 B35 FR



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2025, March 17 - data subject to change