



CoreLine Panel G6

RC132V G6 36S/UE840 PSU W60L60 NOC

CoreLine Panel G6, UltraEfficient, 22.5 W, 600x600 mm, VPC, 3600 lm, 4000 K

Philips CoreLine panel Gen6 delivers on the CoreLine promise of innovation, easy installation, and excellent illumination. Designed as a direct replacement for functional luminaires in general lighting applications, this LED panel light's innovative All-in feature offers a choice of three lumen packages and three-color temperatures in a single luminaire. This makes it easy to select the right product, gives you the flexibility respond to customer preferences on site, and means fewer product codes on stock. Installing the CoreLine RC132V LED panel is quick and easy, using the product's quick connector or flywire. The CoreLine range includes Interact Ready luminaires with integrated wireless communications, ready to be used with Interact gateways, sensors, and software.

Product data

General Information		Stroboscopic effect visibility measure (SVM)	
Number of gear units	1 unit	Stroboscopic effect visibility measure (SVM)	0.4
Driver included	Yes	Beam angle of light source	120 degree(s)
Value ladder	Performance	Light source color	840 neutral white
Safety device	SC [Safety cable]	Optic type	Beam angle 120°
Light Technical		Luminaire light beam spread	120°
Luminous Flux	3,600 lm	Unified glare rating CEN	23
Luminous Efficacy (rated) (Nom)	160 lm/W	Operating and Electrical	
Correlated Color Temperature (Nom)	4000 K	Input Voltage	220 to 240 V
Color rendering index (CRI)	>80	Line Frequency	50 or 60 Hz
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1	Inrush current	20 A
		Inrush time	0.2 ms
		Power Consumption	22.5 W

CoreLine Panel G6

Power Factor (Fraction)	0.9
Connection	Push-in connector 2-pole
Cable	-
Number of products on MCB of 16 A type B	23

Temperature

Ambient temperature range	-10 to +35 °C
---------------------------	---------------

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit external (On/Off)
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Steel
Reflector material	Acrylate
Optic material	Polystyrene
Optical cover material	Polystyrene
Fixation material	-
Housing Color	White RAL 9003
Optical cover finish	Opal
Overall length	595 mm
Overall width	595 mm
Overall height	62 mm
Dimensions (Height x Width x Depth)	62 x 595 x 595 mm
Compatible ceiling or ceiling installation accessory type	Visible profile ceiling version

Approval and Application

Ingress protection code	IP20/44 [Finger-protected; wire-protected, splash-proof]
Mech. impact protection code	IK03 [0.3 J]
Sustainability rating	-
Protection class IEC	Safety class II
Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	CE mark
ENEC mark	ENEC mark

Warranty period	5 years
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes

Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
Initial chromaticity	(0.38, 0.38) SDCM ≤3
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	L90
Lumen maintenance at median useful life* 100000 h	L80

Application Conditions

Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Not applicable

Product Data

Order product name	RC132V G6 36S/UE840 PSU W60L60 NOC
Full product name	RC132V G6 36S/UE840 PSU W60L60 NOC
Full product code	872016974981899
Order code	911401800087
Material Nr. (12NC)	911401800087
Numerator - Quantity Per Pack	1
Net Weight (Piece)	1.720 kg
EAN/UPC - Product/Case	8720169749818
Numerator - Packs per outer box	4
EAN/UPC - Case	8720169750074

CoreLine Panel G6

Dimensional drawing

