

# SLI028027NW\_PW\_CN\_2H\_A

SLI028027NW\_PW\_CN\_2H\_A



Power	<b>75 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>13000 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>10</b>	Degree of protection (IP)	<b>IP65</b>

## Technical data

---

Code	SLI028027NW_PW_CN_2H_A
Power	75 W
Nominal current	332 mA
Voltage	230 V
Energy consumption	75 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.99
Useful luminous flux*	13000 lm (360°)
Luminous flux**	11200 lm (360°)
Lamp efficacy	173 lm/W
Luminous intensity	3600 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	No
Working temperature range	-25/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	10
Degree of protection (IP)	IP65
Colour	Gray/White
Dimension (AxBxC)	1550x72x70 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 10 pcs per line ,