

ALGINE

SLI038018CCT

Smart LED luminaire ALGINE with the possibility of changes to the colour temperature of light (CCT), with the possibility of dimming (DIMM) and remote commissioning and control via the app on your mobile device. Designed for recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

CCT

IK06




Power	6 W	Voltage	230 V
Luminous flux*	520 lm (120°)	Colour temperature	3000-6500 K
Colour of light	CCT	Beam angle	120 °
IK	06	Degree of protection (IP)	IP20

Technical data


Code	SLI038018CCT
Power	6 W
Nominal current	40 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	6 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Useful luminous flux*	520 lm (120°)
Luminous flux**	520 lm (360°)
Lamp efficacy	87 lm/W
Colour temperature	3000-6500 K
Colour of light	CCT
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	SMART
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC, STEEL
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	112x112x35 mm
Mounting hole	105x105 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC

Related documents



 User manual




 Declaration of Conformity



 Photometric file



 3D model

