

PRODUCT-DETAILS

62762-83-WL-500

62762-83-WL-500 WD 180 flex comf. sens. WL



Algemene informatie

Type	62762-83-WL-500
Artikelnummer	2CKA006200A0170
EAN	4011395292235
Omschrijving	62762-83-WL-500 WD 180 flex comf. sens. WL
Omschrijving	<p>Movement detector sensor with with measurement of ambient light. For automatic switching of devices dependent on motion and brightness. Push switch function possible at all times. ./.. In combination with dimmer insert flex: dimming function of lighting and selectable light value storage. With time-controlled basic illumination function. With time-controlled night anti-glare function. With enabling of pre-warning of switch-off for stairwell operation. Compatible with all free@home flex inserts. Works with free@home. Remote operation via the Bluetooth and smartphone/tablet app. Programming via Bluetooth with the ABB-free@home® app or via the web interface of the System Access Point. Extension of the detection range by means of master/slave combination. Timer with Astro function. Automatic switchover from summer time to winter time (switch-off function). With continuous light/continuous Off function. With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Surveillance density: 14 sectors with 56 switching segments. Switch-off delay: approx. 10 sec - 30 min or short-time pulse 1 sec adjustable. For relay insert flex, 1gang, 64811 U. For e-contact insert flex, 1gang, 64814 U. For series relay insert flex, 2gang, 64821 U. For LED touch dimmer insert flex, 1gang, 64851 U.</p>

Installation

Instructies en handleidingen	No document needed
------------------------------	--------------------

Technical

Gegevensblad, technische informatie	No document needed
Geschikt voor	2CKA006800A3042 2CKA006800A3048 2CKA006800A3045 2CKA006500A0013 2CKA006800A3051
Compatibele bussystemen	free@home
Productreeks	flexTronics free@home
Schakelaarprogramma	63x63 future linear Busch-axcent Busch-axcent pur
Minimale schakeltijd	Aan-schakelaar 30 seconde
Montagetype	Inbouw
Materiaal	Thermoplast
Uitvoering klok	Movement sensor
RAL-nummer	RAL 9006 - Blank
Kleur	aluminium zilver
Uitvoering	Lithium
Batterijsoort	Button Cell
Gewicht batterij	0.07 g
Toepassingsgebieden	Elektrische belasting en Lichtregeling

Environmental

Omgevingsluchttemperatuur	-5...45 °C
Beschermingsgraad	IP20
RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS-informatie	2CKA200000E7371
REACH-verklaring	2CKA309999E9999

Dimensions

Product netto breedte	63 mm
Product netto hoogte	63 mm
Product netto diepte	35 mm
Product netto gewicht	34 g

Ordering

Minimale bestelhoeveelheid	1 stuk
Pakketniveau 1 Units	karton 1 stuk
Pakketniveau 1 Brutogewicht	0.106 kg
Nummer douanetarief	85389099
E-Number (Finland)	2815702
Land van herkomst	Germany (DE)

Certificates and Declarations

Conformiteitsverklaring - CE	No declaration needed
---------------------------------	-----------------------

Classifications

ETIM 8	EC000138 - Bewegingssensor-element
ETIM 9	EC000138 - Bewegingssensor-element
WEEE-categorie	5. Small Equipment (No External Dimension More Than 50 cm)
AEEA B2C / B2B	Business To Consumer
CN8	8538 90 99
eClass	V11.0 : 27144008

Categorieën

Laagspanningsproducten en -systemen → Gebouwautomatisering → free@home → User Operation → Gebruikershandleiding - Solo → Bewegingsdetectoren

