



Ledinaire Waterproof Tube Housing

WT050C 1xTLED L1200

- 220 to 240 V - 50 or 60 Hz - Safety class II - - - IP65 | Dust penetration-protected, jet-proof - IK08 | 5 J vandal-protected - White

The Ledinaire waterproof (WT050C) range contains a selection of empty, waterproof housings, that can cater for LED tubes of your choice. It comes with the high Philips quality levels at a competitive price. Ledinaire enables, simple and quick installation, with a choice of single and double tube installations.


Product data

General Information		Mechanical and Housing	
Angle	-	Overall length	1,275 mm
Accessory color	White	Overall width	70 mm
Value ladder	Value	Overall height	84 mm
Light Technical		Dimensions (Height x Width x Depth)	84 x 70 x 1275 mm
Color rendering index (CRI)	-	Material	Polycarbonate
Luminaire light beam spread	-	Approval and Application	
Operating and Electrical		Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Input Voltage	220 to 240 V	Mech. impact protection code	IK08 [5 J vandal-protected]
Line Frequency	50 or 60 Hz	Protection class IEC	Safety class II
Input Frequency	50 or 60 Hz	Product Data	
		Full product code	871016336602999
		Order product name	WT050C 1xTLED L1200

Ledinaire Waterproof Tube Housing

Order code	911401807381
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material number (12NC)	911401807381
Full product name	WT050C 1xTLED L1200

EAN/UPC - Case	8710163366180
----------------	---------------



Dimensional drawing

