

PRODUCT DATASHEET L 36W 865

LUMILUX® T8 | Tubular fluorescent lamps 26 mm, with G13 bases



Areas of application

- Public buildings
- Office lighting
- Industry
- Shops
- Supermarkets and department stores
- Street lighting
- Outdoor applications only in suitable luminaires

Product benefits

- Proven lamp technology

Product features

- Very good lumen maintenance: 90 % throughout the service lifetime of the lamp
- Good color rendering index
- Dimmable

March 24, 2025, 23:49:36 L 36W 865

TECHNICAL DATA

Electrical data

Nominal wattage	36 W
Construction wattage	36.00 W
Nominal voltage	220 V

Photometrical data

Luminous flux	3250 lm
Luminous efficacy	90 lm/W
Light color (designation)	Cool White
Color temperature	6500 K
Color rendering index Ra	> 80
Light color	865

Dimensions & Weight

Overall length	1200.00 mm
Diameter	26.00 mm
Product weight	147.00 g

Additional product data

Base (standard designation)	G13
Mercury content	3.0 mg
Design / version	Frosted

Capabilities

Dimmable	No

Certificates & Standards

Energy efficiency class	A
Energy consumption	42.00 kWh/1000h

Country-specific categorizations

Order reference	L 36W/865

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G13
Length	1200.00 mm

Height	26.00 mm
Width	26.00 mm

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075692992	Sleeve 1	27 mm x 28 mm x 1,210 mm	167.00 g	0.91 dm ³
4058075693005	Shipping box 25	1,234 mm x 150 mm x 155 mm	4510.00 g	28.69 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.