

SLI028024NW_PW_DALI

SLI028024NW_PW_DALI



Power	20 W	Voltage	230 V
Luminous flux*	3250 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
IK	10	Degree of protection (IP)	IP65

Technical data

Code	SLI028024NW_PW_DALI
Power	20 W
Nominal current	150 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.92
Useful luminous flux*	3250 lm (360°)
Luminous flux**	3000 lm (360°)
Lamp efficacy	163 lm/W
Luminous intensity	1000 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	3
Dimmable	DALI
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	POLYCARBONATE
IK	10
Degree of protection (IP)	IP65
Colour	Gray/White
Dimension (AxBxC)	600x72x70 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC
Other	MAX 22 pcs per line ,



Related documents



 Declaration of Conformity

