

# PRODUCT DATASHEET

## Submarine Through Wiring 150cm 19W 4000K

SUBMARINE THROUGHWIRING | Damp-proof luminaire with throughwiring connection

---

### Areas of application

- Basements, garages, warehouses
- For indoor use only



---

### Product benefits

- Easy installation, no tools required for connection
- Quick and easy lamp replacement
- Good, even illumination
- Easy installation on wall and ceiling with through-wiring option
- Quick and easy wiring, due to tool-free housing opening

---

### Product features

- Durable and energy-saving LED luminaire
- Dust-protected and jet-proof (IP65)
- Pre-assembled through wiring kit
- Through Wiring Kit: 3 x 1.5 mm with fast connector
- Through-wiring 3x1.5mm<sup>2</sup> already installed



## TECHNICAL DATA

### Electrical data

Nominal wattage	19.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Inrush current	7.5 A
Total harmonic distortion	≤ 20 %
Protection class	I
Operating mode	Mains voltage

### Photometrical data

Luminous flux	1900 lm
Total luminous flux of contained light sources	2200 lm
Luminous efficacy	105 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥80
Standard deviation of color matching	≤6 sdc <sub>m</sub>
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0
Beam angle	140 °

### Dimensions & Weight

Length	1561.00 mm
Width	66.00 mm
Height	75.00 mm
Product weight	1380.00 g

---

Product line drawing with numbers

---

Product line drawing with numbers

### Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Plastic
Cover material	Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-20...+35 °C
Temperature range at storage	-20...+80 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP65
Protection class IK (shock resistance)	IK06
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Lifespan L80/B10 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	100000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### Certificates & Standards

Standards	CE / EMC / UKCA
Luminaire with limited surface temperature, "D sign"	No

### Additional product data

Number of illuminants	1
-----------------------	---

### EQUIPMENT / ACCESSORIES

- Through-wiring cable kit included

### DOWNLOAD DATA

**Documents and certificates**

User instruction



Declarations Of Conformity CE



Declarations Of Conformity UKCA

**LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075576452	Folding box 1	77 mm x 71 mm x 1,565 mm	1657.00 g	8.56 dm <sup>3</sup>
4058075576469	Shipping box 6	1,582 mm x 235 mm x 182 mm	11173.00 g	67.66 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.