


# Centurion Bulkhead



- High lumen performance LED polycarbonate bulkhead for increased spacings
- Supplied with self-adhesive legend
- Self-test as standard
- 20mm conduit entry positions and rear terminal box entry
- Hinged screwless gear tray for ease of installation
- Viewing distance 18 metres



***	Escape route 2 metres wide (1 Lux minimum) *			
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5	1.7	7	2	6.8
4	2	8.5	2.5	8
6	-	-	-	-

***	Open (Anti-Panic) area (0.5 Lux Minimum) **			
Mounting Height (M)	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
2.5	2.5	7.5	2.5	7.5
4	3.5	9	3.5	9
6	3.6	9.5	3.6	9.5

INPUT	HERTZ	TEMP	LIFETIME (HRS)	BEAM ANGLE	CLASS	IP	IK
230V	50Hz	0°C to 40°C	L70 50,000	110°	1	IP65	IK08

CODE	DESCRIPTION	WATTAGE	CCT	STANDARD MODE	EMERGENCY MODE	TRADE
ACELED/3M/ST	Daylight - Maintained / Non-Maintained	3W	6500K	261lm	177.7lm	£77.50

CODE (ACCESSORIES)	DESCRIPTION	TRADE
ASBP/2/LI	3.2V 2000mAh Li-FePO4 Replacement Battery	£9.25