

SLI029075CW_PW

SLI029075CW_PW

IP65

IK07




| | | | |
|-----------------|-----------------------|---------------------------|---------------|
| Power | 20 W | Voltage | 230 V |
| Luminous flux* | 1650 lm (120°) | Colour temperature | 6000 K |
| Colour of light | CW | Beam angle | 100 ° |
| IK | 07 | Degree of protection (IP) | IP65 |

Technical data

| | |
|------------------------------|-----------------|
| Code | SLI029075CW_PW |
| Power | 20 W |
| Nominal current | 95 mA |
| Voltage | 230 V |
| Energy consumption | 20 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 1650 lm (120°) |
| Luminous flux** | 1650 lm (360°) |
| Lamp efficacy | 83 lm/W |
| Colour temperature | 6000 K |
| Colour of light | CW |
| Beam angle | 100 ° |
| RA | >70 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | Aluminum, GLASS |
| IK | 07 |
| Degree of protection (IP) | IP65 |
| Colour | White |
| Dimension (AxBxC) | 116x92x24 mm |
| For use | Outside |
| Assembly method | On the ceiling |
| Application | EXT |
| Made in | PRC |

Related documents



 User manual



 Declaration of Conformity

