

# ALGINE

SLI035041NW

LED panel ALGINE, with a power of 45 W, high light efficacy 100 lm/W. It is made of high-quality components, supported by a 5-year warranty. Lights up with neutral light - the most universal colour (4000K), which is suitable for the rooms we use on a daily basis, ensuring comfort during everyday activities. Suitable for surface, recessed and suspended mounting.



---

Power	<b>45 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>4500 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Degree of protection (IP)	<b>IP20</b>

---


## Technical data

Code	SLI035041NW
Power	45 W
Nominal current	190 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	45 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	4500 lm (120°)
Luminous flux**	4500 lm (360°)
Lamp efficacy	100 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	295x1195x10 mm
Mounting hole	275x1175 mm
For use	Inside
Assembly method	Recessed, On the ceiling, Suspended
Application	INT
Made in	PRC



## Related documents



 User manual



 Declaration of Conformity



 Photometric file

