

Empty enclosure

TKS 2518-12TE



TKS 2518-12TE

Empty enclosure

Productnumber: 14300201

Dimensions: 254 x 180 x 111 mm

Empty enclosure, protection class IP30, Polycarbonate, internal fixing points, for standard indoor installations, for mounting up to 22 WINSTA® plug connectors in conjunction with TKS AP adapter frames

12 Modular units, Box: Polycarbonate, grey, Lid: Polycarbonate, grey



Technical Data

electrical characteristics

Rated operating voltage AC:	690 V
Rated operating voltage DC:	1000 V
Protection class:	II
Type of protection:	IP30
vented:	no
Number of modules:	12
UL Type Rating:	not specified

Colours

Base unit colour:	grey
Cover colour:	grey

Dimensions

Width:	254 mm
Length:	180 mm
Height:	111 mm
Weight:	0.342 kg

Material characteristics

UV-resistant:	yes
Halogen free:	yes
Flammability class according with UL94:	V2
Glow-wire flammability according to EN 60695-2-11:	960 °C

mechanical properties

Type of fastening:	Wall/ceiling mounting
Impact strength:	IK07
Sealable:	yes
Cover screw torque:	1.2 Nm

mechanical properties

Flange variant:	no
Type of top part:	Cover
Fastening:	internal fixing points

Ambient conditions

max. relative humidity 25°C:	95 %
max. relative humidity 40°C:	50 %
Min. ambient temperature:	-35 °C
Max. ambient temperature:	80 °C
24h ambient temperature:	60 °C
Installation location:	Indoors

Sales Information

EAN:	4013902694310
Packing Unit Code:	C62
ETIM Class:	EC000261
Custom tariff number:	85389099

Material

Base unit material:	Polycarbonate
Cover material:	Polycarbonate
Cover screw material:	Polyamide, glass-fibre reinforced

Accessories

[19814401 - NS 35-144 - Standard rail](#)

[19817101 - NS 35-171 - Standard rail](#)

[19400101 - TK ABL - External fixing lugs kit](#)

[89603201 - MABF 150-3 - Mast/pipe fixing set](#)

[89604101 - MABF 215-2 - Mast/pipe fixing set](#)

[19500801 - TK MPI-2518 - Mounting plate](#)

[19700801 - TK MPS-2518 - Mounting plate](#)

Cable gland

