


# Osprey Lithium High Rack Bulkhead



- Modern slim profile IP65 LED polycarbonate bulkhead
- Compact high polished reflector design to provide required light level from high mounting heights
- High performance LED's and optical performance allows increased spacing ratios
- Self-test as standard
- Aesthetically designed for modern appearance
- 20mm side and rear cable entries



***	Escape route 2 metres wide (1 Lux minimum) *			
	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
10	-	-	4.5	20
15	-	-	2.5	17

***	Open (Anti-Panic) area (0.5 Lux Minimum)**			
	Transverse to Wall	Transverse to Transverse	Axial to Wall	Axial to Axial
10	5.2	14.5	5.2	14.5
15	5.2	18	5.2	18

INPUT	HERTZ	TEMP	LIFETIME (HRS)	BEAM ANGLE	CLASS	IP	IK
230V	50Hz	0°C to 40°C	L70 50,000	60°x100°	1	IP65	IK08

CODE	DESCRIPTION	WATTAGE	CCT	STANDARD MODE	EMERGENCY MODE	TRADE
AOSLED/3M/ST	Maintained / Non-Maintained	8.3W	6500K	550lm	405lm	£79.00

CODE (ACCESSORIES)	DESCRIPTION	TRADE
ASBP/15/LI	6.4V 5500mAh-5 Li-FeP04 Replacement Battery	£21.80

