

LED CANDLE

WOJ+14650

LED source LED CANDLE 6 W with E-14 base and in the shape of a glass 'candle'. It is even more energy-efficient thanks to the use of durable COG filaments, which consume very little electricity. It shines with a very warm light (1800K), which promotes relaxation and rest, making the illuminated room cosier. Wide beam angle 300° ensures even illumination of the room.




| | | | |
|-----------------|----------------------|---------------------------|---------------|
| Power | 6 W | Voltage | 230 V |
| Luminous flux** | 540 lm (360°) | Colour temperature | 1800 K |
| Colour of light | WW | Beam angle | 300 ° |
| Socket | E14 | Degree of protection (IP) | IP20 |

Technical data

| | |
|------------------------------|---------------|
| Code | W0J+14650 |
| Power | 6 W |
| Nominal current | 36 mA |
| Voltage | 230 V |
| Energy consumption | 6 kWh/1000h |
| Frequency | 50HZ Hz |
| Power factor | 0.65 |
| Useful luminous flux* | 540 lm (360°) |
| Luminous flux** | 540 lm (360°) |
| Lamp efficacy | 90 lm/W |
| Colour temperature | 1800 K |
| Colour of light | WW |
| Beam angle | 300 ° |
| RA | 80 |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | +40/-20 ° |
| Lifespan | 17000 h |
| Socket | E14 |
| Degree of protection (IP) | IP20 |
| Dimension (AxBxC) | 35x98 mm |
| Made in | PRC |

Related documents



 Declaration of Conformity

