

PRODUCT-DETAILS

DPCA100C32/030

DPCA100C32/030 Residual Current Circuit Breaker with Overcurrent Protection



General Information	
Extended Product Type	DPCA100C32/030
Product ID	2CDB333201R1324
EAN	5413656115410
Catalog Description	DPCA100C32/030 Residual Current Circuit Breaker with Overcurrent Protection
Long Description	DPCA100C32/030 Residual Current Circuit Breaker with Overcurrent Protection

Eco Transparency	
Environmental Product	9AKK108467A5738
Declaration - EPD	

Technical	
Standards	IEC/EN 61009-1
Tripping Characteristic	С
Type of Residual Current	А
Rated Operational Voltage	230 V AC acc. to IEC 60898-1 230 V
Rated Insulation Voltage (U _i)	500 V acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV

DPCA100C32/030 2

Primary Rated Impulse Withstand Voltage	4 kV
Input Voltage Type	AC
Rated Current (In)	32 A
Rated Residual Current	30 mA
Rated Short-Circuit Capacity	10 kA
Rated Ultimate Short- Circuit Breaking Capacity (I _{cu})	10 kA
Rated Service Short- Circuit Breaking Capacity, in % of Icu (I _{cs})	8 kA
Leakage Current Type	A
Frequency (f)	50 Hz
Rated Frequency (f)	50 Hz
Energy Limiting Class	3
Number of Poles	2
Number of Protected Poles	2
Overvoltage Category	III
Earthing Switch Type	Undelayed
Accessories Available	Yes
Number of Batteries	0
Rated Cross-Section	1 - Solid-Core 1 35 mm² 4 - Multi-Wired 1 25 mm²

Environmental	
Ambient Air Temperature	Operation -25 +55 °C
Degree of Protection	IP20
Pollution Degree	3
RoHS Status	Following EU Directive 2011/65/EU
RoHS Information	9AKK107991A0946
SCIP	16d43f0f-58e2-46e4-9af9-ecaae7a78c5e Poland (PL)

Technical UL/CSA	
Short-Circuit Current	0 A
Rating (SCCR)	

Dimensions	
Width in Number of Modular Spacings	2
Product Net Width	0.036 m
Product Net Height	0.09 m
Product Net Depth / Length	0.072 m
Product Net Weight	0.22 kg
Built-In Depth (t ₂)	72 mm

Ordering	
Minimum Order Quantity	1 piece

DPCA100C32/030 3

Package Level 1 Units	pack 1 piece
Package Level 1 Gross	0.236 kg
Weight	

Certificates and Declarations

Certification Agency	IEC
	EN
Declaration of	No declaration needed
Conformity - CF	

Installation

Instructions and	No document needed
Manuals	

Popular Downloads

Data Sheet, Technical	No document needed
Information	

Classifications

ETIM 8	EC000905 - Earth leakage circuit breaker
ETIM 9	EC000905 - Earth leakage circuit breaker
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	8536 20 10
UNSPSC	39121614
eClass	V11.0 : 27142207
Object Classification	Q
Code	

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow ABB\ VY \rightarrow RCD\ ABB\ VY \rightarrow DPC100\ ABB\ VY \rightarrow DPC10$

