Product Data Sheet GW68561


68 ACS Range



The distribution board for construction sites type Q-BOX are designed to withstand the effects of wear, impact and the stress caused by atmosph. They come in pre-wired versions fitted with interlocked socketoutlets (with or without a fuse-holder) up to 63Å, or socket-outlets type IEC 309.. The wired versions are also equipped with accessories like the emergency push-button, lockable doors, stainless steel tear-proof cablefastening hooks, and built-in transportation handles on the upper part of the board. To ensure the best possible positioning on the construction site, 68 Q-BOX ACS boards can be surface-mounted, floor-mounted or fitted on poles.

Туре	Q-BOX 4 ACS	board type	Wired
Colour	Light blue	Outer dim. LxHxD (mm)	636x821x400
Weight (kg)	22	Accordance with Standards	EN 61439-4 (ACS)
Characteristics	UV resistance (EN 62208)	IP degree	IP55
Mechanical resistance	IK10	Glow wire test	650 °C
Thermo-pressure with ball	70 °C	Insulation class	I
Power supply	Terminal block	No. of poles	2P+E
Power suppliable (kW)	6	Mains switch	RCBO 32A 2P 6 kA 0,03A - AC type
Circuits protection	MCB	No. socket outlets	4
Socket-outlet 2P+E 16A - IB	4	Emergency push-button	Yes
Electrocod	139		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS											
Saline solution	Acids		Bases		Solvents			Mineral	UV		
	Concentrated	Diluited	Concentrated	Diluited	Hexane	Benzol	Acetone	Ethyl alcohol	oil	rays	
Resistant	Limited resistance	R <mark>esista</mark> nt	Limited resistance	R <mark>esista</mark> nt	Limited res <mark>istan</mark> ce	Limited resistance	Li <mark>mit</mark> ed resi <mark>stan</mark> ce	Resistant	Li <mark>mite</mark> d res <mark>istan</mark> ce	Resistant	



DIMENSIONAL

TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

CE

GEWISS S.p.A. Via A. Volta, 1 24069 Cenate Sotto - Bergamo - Italy tel. +39 035 94 61 11 fax +39 035 94 69 09