


## SZ HH 1500 (765 042)

- 20° angled operating head for HH fuses that are not easily accessible



Type	SZ HH 1500
Part No.	765 042
Nominal voltage (U <sub>N</sub> )	1 ... 36 kV
Clamping range	30 ... 50 <sup>1)</sup> / 50 ... 90 mm
Total length (l <sub>G</sub> )	1500 mm
Insulating clearance (l <sub>i</sub> )	525 mm
Length (handle) (l <sub>H</sub> )	790 mm
Insertion depth (l <sub>o</sub> )	185 mm
Standard	DIN VDE V 0681-3
For use at	*
For	Indoor and outdoor installations
Design	Straight clamp body
Material (insulating stick)	Glass-fibre reinforced polyester tube
Material (operating head)	Glass-fibre reinforced polyamide
Material (reducing insert)	Polyamide
Material (adjustable handle)	Polyamide
Diameter	43 mm
Colour	Grey *
Anti-rotation plug-in coupling including end fitting	No
Type of device	Fuse tong
Weight	2,59 kg
Customs tariff number	82055980
GTIN	4013364093775
PU	1 Stk

<sup>1)</sup> Only if used with reducing insert

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.