


Produktdetails

62764-866-WL-500

62764-866-WL-500 WD 180 flex multi sens. WL




---

### Allgemeine Informationen

Typ	62764-866-WL-500
Bestellnummer	2CKA006200A0249
EAN	4011395292723
Beschreibung	62764-866-WL-500 WD 180 flex multi sens. WL

Langbeschreibung	<p>Movement detector sensor with with measurement of ambient light. For automatic switching of devices dependent on motion and brightness. Push switch function possible at all times.</p> <p>For detection down to the floor. For detection in stairwells. With 4 detection levels. In combination with dimmer insert flex: dimming function of lighting and selectable light value storage. With time-controlled basic illumination function. With time-controlled night anti-glare function. With enabling of pre-warning of switch-off for stairwell operation. Compatible with all free@home flex inserts. Remote operation via the Bluetooth and smartphone/tablet app.</p> <p>Multi-lens: suitable also for mounting heights of 2.20 m. Extension of the detection range by means of master/slave combination. Timer with Astro function. Automatic switchover from summer time to winter time (switch-off function). With continuous light/continuous Off function. With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Surveillance density: 54 sectors with 224 switching segments. Switch-off delay: approx. 10 sec - 30 min or short-time pulse 1 sec adjustable. For relay insert flex, 1gang, 64811 U. For e-contact insert flex, 1gang, 64814 U. For series relay insert flex, 2gang, 64821 U.</p>
------------------	---

---

### Installation / Montage

Betriebs- und Montageanleitung	No document needed
--------------------------------	--------------------

## Technische Daten

Datenblatt, technische Information	No document needed
Geeignet für	2CKA006800A3042 2CKA006800A3048 2CKA006800A3045 2CKA006500A0013 2CKA006800A3051
Unterstützte Bussysteme	free@home
Produktreihe	Busch-flexTronics® Busch-free@home®
Minimalste Umschaltzeit	einschalten 30 Sekunde(n)
Montageart	Flush Mounted
Werkstoff	Thermoplastischer Kunststoff
Ausführung	Bewegungssensor
Farbe	Edelstahl
Chemische Batteriezusammensetzung	Lithium, nicht aufladbar
Batterieart	Knopfzelle
Batteriegewicht	0.07 g
Anwendungsbereich	Elektrische Last- und Lichtsteuerung

## Umwelt

Umgebungstemperatur	-5...45 °C
Schutzart	IP20
RoHS Status	nach EU-Richtlinie 2015/863 22. Juli 2019 (RoHS 3)
RoHS Information	2CKA200000E7438
REACH Erklärung	2CKA309999E9999

## Abmessungen

Breite des Produkts	63 mm
Höhe des Produkts	63 mm
Tiefe des Produkts	44 mm
Nettogewicht	34 g

## Bestelldaten

Mindestbestellmenge	1 Stück
Menge Verpackungseinheit 1	Karton 1 Stück
Bruttogewicht Verpackungseinheit 1	0.105 kg
Zolltarifnummer	85389099
Herkunftsland	Deutschland (DE)

---

## Zertifikate und Deklarationen

---

Konformitätserklärung -  
CE

No declaration needed

---



---

## Klassifizierungen

---

ETIM 8	EC000138 - Bewegungsmelder-Sensor
ETIM 9	EC000138 - Bewegungsmelder-Sensor
WEEE Kategorie	5. Geräte, bei denen keine der äußeren Abmessungen mehr als 50 cm beträgt (Kleingeräte)
WEEE B2C / B2B	B2C
CN8	8538 90 99
eClass	V11.0 : 27144008

---



---

## Kategorien

---

Niederspannungsprodukte und Systeme → Haus- und Gebäudeautomation → free@home → Bedienen → Solo → Bewegungsmelder

