



# TownGuide Performer

## BDP100 LED50/740 II DS PCF GR 62P

BDP100 | TOWNGUIDE PERF FLAT CONE - LED50 | LED module 5000 lm - 740 neutral white - Safety class II - Distribution symmetrical - Polycarbonate bowl/cover frosted - Post-top for diameter 62 mm

The TownGuide Performer family consists of six recognizable, yet modern shapes: Flat Cone, Bowl, Classic Cone, Classic T, T and Tzero. Each luminaire has the option of a clear (PCC), translucent (PCTR) or frosted (PCF) bowl (except Tzero, which is only available with a clear bowl). With an extensive range of lumen packages, neutral white or warm white LED lights sources, and a range of dedicated optics for lower mounting heights, it's easy to select the version that best suits the specific requirements of your project. All this combined with a long life expectancy of 100,000 operating hours. In addition, TownGuide Performer has a variety of control system options that can make this luminaire an integral part of smart energy-reduction programs. This includes LumiStep, DynaDimmer, and LineSwitch stand-alone dim control, and Coded Mains group control, right up to seamless remote connectivity with Interact lighting management software. Installation is easy. Thanks to the bayonet whistle connector with integrated gland located in the spigot, there's no need to open the luminaire for installation. The Signify Service tag app offers direct access to all relevant data, ensuring maintenance is easy too. Philips has made every effort to make the Total Cost of Ownership (TCO) of the luminaire as attractive as possible. And as TownGuide Performer is a dedicated LED luminaire, compatible with a variety of control systems, there are significant energy and maintenance cost savings compared with conventional lighting.

### Product data

| General Information |                            | Light source replaceable |        |
|---------------------|----------------------------|--------------------------|--------|
| Lamp family code    | LED50 [LED module 5000 lm] | Number of gear units     | 1 unit |

# TownGuide Performer

|                          |                                   |
|--------------------------|-----------------------------------|
| Driver included          | Yes                               |
| Light source engine type | LED                               |
| Service tag              | Yes                               |
| Product family code      | BDP100 [TOWNGUIDE PERF FLAT CONE] |
| Lighting Technology      | LED                               |
| Value ladder             | Performance                       |

## Light Technical

|                                    |                                  |
|------------------------------------|----------------------------------|
| Upward light output ratio          | 3                                |
| Luminous Flux                      | 2,800 lumen                      |
| Standard tilt angle posttop        | 0°                               |
| Standard tilt angle side entry     | -                                |
| Correlated Color Temperature (Nom) | 4000 K                           |
| Luminous Efficacy (rated) (Nom)    | 82 lm/W                          |
| Color rendering index (CRI)        | 70                               |
| Light source color                 | 740 neutral white                |
| Optical cover/lens type            | Polycarbonate bowl/cover frosted |
| Luminaire light beam spread        | 75°                              |
| Optic type outdoor                 | Distribution symmetrical         |

## Operating and Electrical

|  |                               |
|--|-------------------------------|
| Input Voltage                            | 220-240 V                     |
| Line Frequency                           | 50 to 60 Hz                   |
| Input Frequency                          | 50 to 60 Hz                   |
| Power Consumption                        | 34 W                          |
| Inrush current                           | 45 A                          |
| Inrush time                              | 0.285 ms                      |
| Power Factor (Fraction)                  | 0.94                          |
| Connection                               | Screw connection block 5-pole |
| Cable                                    | -                             |
| Number of products on MCB of 16 A type B | 10                            |

## Temperature

|                           |               |
|---------------------------|---------------|
| Ambient temperature range | -40 to +35 °C |
|---------------------------|---------------|

## Controls and Dimming

|                               |                              |
|-------------------------------|------------------------------|
| Dimmable                      | No                           |
| Driver/power unit/transformer | Power supply unit regulating |
| Control interface             | -                            |
| Constant light output         | No                           |

## Mechanical and Housing

|                             |                             |
|-----------------------------|-----------------------------|
| Housing Material            | Aluminum                    |
| Reflector material          | -                           |
| Optic material              | Acrylate                    |
| Optical cover/lens material | Polycarbonate               |
| Fixation material           | Steel                       |
| Housing Color               | Gray                        |
| Mounting device             | Post-top for diameter 62 mm |

|                           |              |
|---------------------------|--------------|
| Optical cover/lens shape  | Conical flat |
| Optical cover/lens finish | Frosted      |
| Overall height            | 209 mm       |
| Overall diameter          | 570 mm       |
| Effective projected area  | 0.051 m²     |

## Approval and Application

|  |  |
|--|--|
| Ingress protection code                | IP66 [Dust penetration-protected, jet-proof]                                       |
| Mech. impact protection code           | IK10 [20 J vandal-resistant]   |
| Surge Protection (Common/Differential) | Luminaire surge protection level until 6 kV differential mode and 6 kV common mode |
| Sustainability rating                  | -  |
| Protection class IEC                   | Safety class II  |
| Flammability mark                      | -  |
| CE mark                                | Yes  |
| ENEC mark                              | ENEC mark  |
| Warranty period                        | 5 years  |
| EU RoHS compliant                      | Yes  |

## Initial Performance (IEC Compliant)

|                                       |                      |
|---------------------------------------|----------------------|
| Luminous flux tolerance               | +/-7%                |
| Initial chromaticity                  | (0.38, 0.38) SDCM <5 |
| Power consumption tolerance           | +/-10%               |
| Init. Color Rendering Index Tolerance | +/-2                 |

## Over Time Performance (IEC Compliant)

|  |       |
|--|-------|
| Driver failure rate at 5000 h                            | 0.5 % |
| Control gear failure rate at median useful life 100000 h | 10 %  |
| Lumen maintenance at median useful life* 100000 h        | 93    |

## Application Conditions

|                                    |                |
|------------------------------------|----------------|
| Performance ambient temperature Tq | 25 °C          |
| Maximum dim level                  | Not applicable |

## Product Data

|                                 |                                   |
|---------------------------------|-----------------------------------|
| Full product code               | 871829190982800                   |
| Order product name              | BDP100 LED50/740 II DS PCF GR 62P |
| Order code                      | 910925866286                      |
| Numerator - Quantity Per Pack   | 1                                 |
| Numerator - Packs per outer box | 1                                 |
| Material number (12NC)          | 910925866286                      |
| Full product name               | BDP100 LED50/740 II DS PCF GR 62P |
| EAN/UPC - Case                  | 8718291909828                     |



## TownGuide Performer

### Dimensional drawing

