

# ALGINE BACKLIGHT CCT

SLI035075CCT\_PW

LED panel ALGINE BACKLIGHT CCT with the possibility of changing the light color (CCT), with power regulation on the power supply (25/40/45 W), high light efficacy 144 lm/W. Thanks to the ability to change the color temperature (CCT) in the range from 3000K to 6000K, we can adjust the light color depending on our needs and preferences. It is made of high-quality components, supported by a 5-year warranty. The CCT function allows you to changes to the colour temperature of light (3000/4000/6000K). Narrow beam angle 90° gives directional light so that selected objects or surfaces can be better exposed. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	<b>25/40/45 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>6500 lm (360°)</b>	Colour temperature	<b>3000/4000/6000 K</b>
Colour of light	<b>CCT</b>	Beam angle	<b>90 °</b>
Degree of protection (IP)	<b>IP20</b>		

## Technical data

---

Code	SLI035075CCT_PW
Power	25/40/45 W
Nominal current	200 mA
Voltage	230 V
Energy consumption	45 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	6500 lm (360°)
Luminous flux**	3000/4800/5400 lm (360°)
Lamp efficacy	144 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	90 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	620x620x34 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

## Related documents

---



 Declaration of Conformity

---

