





# MASTER UltraEfficient LED bulb

# MAS LEDBulbND7.3-100W E27 840 A60 CL GUE

This is the most efficient LED bulb from Philips brand. 210lm/W helps to concrete the company statement of sustainability. 50000 hour lifetime helps to extend the replacement cycle to reduce the waste. This is not only the high SPEC product, but also keep the light quality of Philips brand

### **Product data**

General Information	
Cap-Base	E27
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	1,535 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	210 lm/W
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Photobiological safety according to EN 62471 RG1			
Photobiological safety according to Liv 024.	7 Not		
Operating and Electrical			
Line Frequency	50 to 60 Hz		
Input Frequency	50 to 60 Hz		
Power Consumption	7.3 W		
Lamp Current (Nom)	71 mA		
Wattage Equivalent	100 W		
Starting Time (Nom)	0.5 s		
Warm-up time to 60% light	0.5 s		
Power Factor (Fraction)	0.4		
Voltage (Nom)	220-240 V		
Temperature			
T-Case Maximum (Nom)	70 °C		


Datasheet, 2025, March 17 data subject to change

# **MASTER UltraEfficient LED bulb**

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Glass
Bulb Shape	A60
Net Weight (Piece)	0.035 kg
Approval and Application	
Energy Efficiency Class	А
Energy Consumption kWh/1000 h	8 kWh
EPREL Registration Number	1442629
Photobiological risk	Photobiological risk group 1 @ 200mm to
	EN62471
EU RoHS compliant	Yes
EyeComfort	Yes
Flickering value (PstLM) - Flickering value as	1
per EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	0.4


Ambient temperature range	-20 to +45 °C
Application Conditions	
can it be used in closed luminaires	No
Product Data	
Order product name	MAS LEDBulbND7.3-100W E27 840 A60
	CL GUE
Full product name	MAS LEDBulbND7.3-100W E27 840 A60
	CL GUE
Full product code	872016918885300
Order code	929003625502
Material Nr. (12NC)	929003625502
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169188853
Numerator - Packs per outer box	10
EAN/UPC - Case	8720169188860


# Dimensional drawing



Product	D	С
MAS LEDBulbND7.3-100W E27 840 A60 CL GUE	60 mm	104 mm

### Photometric data






Spectral Power Distribution Colour - MAS LEDBulbND7.3-100W E27 840 A60 CL GUE

General uniform lighting - MAS LEDBulbND7.3-100W E27 840 A60 CL GUE


# **MASTER UltraEfficient LED bulb**


### Photometric data



Light Distribution Diagram - MAS LEDBulbND7.3-100W E27 840 A60 CL GUE

### Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - MAS LEDBulbND7.3-100W E27 840 A60 CL GUE



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.