

SR D50 5000 FSP1000 IA SA HVIP GFK AL (105 515)




Figure without obligation

Supporting tube with interior sealing end and EB spring element. Air-termination tip $\varnothing 10$ mm.

| Type | SR D50 5000 FSP1000 IA SA HVIP GFK AL |
|--|---------------------------------------|
| Part No. | 105 515 |
| Material of air-termination tip | Al |
| Length of air-termination tip | 1000 mm |
| Material of supporting tube | GRP / Al |
| Length of supporting tube | 5000 mm |
| Outside diameter \varnothing | 50 mm |
| Transport length | 5000 mm |
| Wall thickness | 4 mm |
| Material factor km | 0.7 |
| Length of insulating clearance | 1800 mm |
| Permanent temperature range | -50 °C ... +100 °C |
| Type | UV-stabilised |
| Sleeve | 60 x 5 mm |
| Suitable for installation outside the tube | yes |
| Standard | DIN IEC/TS 62561-8 (VDE V 0185-561-8) |
| Weight | 7,84 kg |
| Customs tariff number | 85389099 |
| GTIN | 4013364271821 |
| PU | 1 Stk |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.