


BCO ML2 BE 180 (927 227)


- LifeCheck arrester monitoring and integrated status indication
- Modular two-pole arrester for optimal protection of two single lines
- For installation in conformity with the lightning protection zone concept at the boundaries from $0_A -2$ and higher



Figure without obligation



Basic circuit diagram BCO ML2 BE 180



Dimension drawing BCO ML2 BE 180

Space-saving, modular combined arrester with a width of 6 mm and push-in connection technology with status indication for protecting two single lines sharing a common reference potential as well as unbalanced interfaces. With signal disconnection for maintenance purposes.

Type	BCO ML2 BE 180
Part No.	927 227
SPD class	TYPE II PI
Impulse category	D1, C1, C2, C3, B2
Nominal voltage (U_N)	180 V
Max. continuous operating voltage (d.c.) (U_C)	180 V
Max. continuous operating voltage (a.c.) (U_C)	127 V
Nominal current at 70 °C (I_N)	0.5 A
Nominal current at 40 °C (I_N)	0.75 A
D1 Total lightning impulse current (10/350 μ s) (I_{imp})	3 kA
D1 Lightning impulse current (10/350 μ s) per line (I_{imp})	1.5 kA
C2 Total nominal discharge current (8/20 μ s) (I_n)	10 kA
C2 Nominal discharge current (8/20 μ s) per line (I_n)	5 kA
Voltage protection level line-line for I_n C2 (U_p)	≤ 630 V
Voltage protection level line-PG for I_n C2 (U_p)	≤ 450 V
Voltage protection level line-line for I_n C1 (U_p)	≤ 630 V
Voltage protection level line-PG for I_n C1 (U_p)	≤ 450 V
Voltage protection level line-line at 1 kV/ μ s C3 (U_p)	≤ 460 V
Voltage protection level line-PG at 1 kV/ μ s C3 (U_p)	≤ 230 V
Series resistance per line	1.8 ohm(s)
Cut-off frequency line-line (f_c)	10 MHz
Capacitance line-line (C)	≤ 250 pF pF
Capacitance line-PG (C)	≤ 450 pF pF
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / red
Degree of protection	IP 20
Connection (input / output)	push-in / push-in
Cross-sectional area (solid)	0.2-2.5 mm ²
Cross-sectional area (flexible)	0.2-2.5 mm ²
Earthing via	35 mm DIN rails acc. to EN 60715
Enclosure material	polyamide PA 6.6
Colour	yellow
Test standards	IEC 61643-21 / EN 61643-21
Approvals	UL
Extended technical data:	-----
- Max. discharge current (8/20 μ s) [1/2 - PG], [1+2 - PG] (I_{max})	20 kA
- Discharge current (8/20 μ s) [1/2 - PG], [1+2 - PG]	10 kA (10x)
- Voltage protection level line-PG at 1 kV/ μ s C3 after being subjected to I_{max} (U_p)	≤ 230 V
Weight	34 g
Customs tariff number	85363010
GTIN	4013364468658
PU	1 Stk

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.