

SLI028030NW

SLI028030NW

Hermetic luminaire LIMEA MINI, with a power of 36 W, high light efficacy 111 lm/W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK07 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

IP65

IK07



Power	36 W	Voltage	230 V
Luminous flux*	4000 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
IK	07	Degree of protection (IP)	IP65

Technical data


Code	SLI028030NW
Power	36 W
Nominal current	170 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.9
Useful luminous flux*	4000 lm (360°)
Luminous flux**	4000 lm (360°)
Lamp efficacy	111 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	plastic
IK	07
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	1223x53x28 mm
For use	Inside/Outside
Assembly method	On the ceiling, Suspended
Application	INT/EXT
Made in	PRC

Related documents



 User manual



 Declaration of Conformity



 Photometric file

